

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	K-3881 & K-5117

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE **APPLICATION FOR PERMIT - ** (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tenneco Oil Company	8. Farm or Lease Name Sawyer State
3. Address of Operator Box 1031, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER D 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 16 TOWNSHIP 9S RANGE 36E NMPM.	10. Field and Pool, or Wildcat Vada Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4065 GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-9-71 Pumped 200 sks. Class "H" cement from 9907'-8143':
3-23-71 Shot 5 1/2" casing at 8000' and recovered same.
3-28-71 Set 100 sk cement plug from 8060'-7720', 100 sk plug from 5630'-5330', 100 sk plug from 4267'-3975' across 8 3/8" casing shoe.
3-30-71 Shot 8 3/8" casing at 1300'. Pulled and recovered same.
4-2-71 Spotted 100 sack cement plug from 1282'-1238', 70 sack plug from 384'-292'. Set 10' plug in surface casing & erected dry hole marker. PLUGGED AND ABANDONED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Conley Watkins TITLE Sr. Prod. Clerk DATE 4/2/71
APPROVED BY [Signature] TITLE SUPERVISOR DISTRICT DATE APR 5 1971
CONDITIONS OF APPROVAL, IF ANY: JAN 24 1972

RECEIVED

APR 6 1971

**OIL CONSERVATION COMM.
HOBBS, N. M.**