

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
LG 5999

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Dry Hole	7. Unit Agreement Name
2. Name of Operator The Dow Chemical Company	8. Farm or Lease Name State "16"
3. Address of Operator 1123 Wilco Building, Midland, Texas 79701	9. Well No. #1
4. Location of Well UNIT LETTER I , 660 FEET FROM THE East LINE AND 1980 FEET FROM THE South LINE, SECTION 16 TOWNSHIP 10S RANGE 36E N.M.P.M.	10. Field and Pool, or Wildcat Crossroads-Devonian South
15. Elevation (Show whether DF, RT, GR, etc.) 4015.2 GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-1/2" Casing set at 5050'. Plugback Depth 5016'. Commenced plugging operations 8/30/79.
 Set 30 sack Class "C" cement plug in 5-1/2" casing from 3736' to 4986'.
 (across perforations 4909'; 4913-1/2'; 4916'; 4918-1/2'; 4920-1/2'; 4923'; 4924'; 4925'; 4926' - 9 holes).
 Set 30 sack Class "C" cement plug in 5-1/2" casing from 2550' to 2800'.
 Set 30 sack Class "C" cement plug in 5-1/2" casing from 2115' to 2365'.
 Set 10 sack Class "C" cement plug in top of 5-1/2" casing from 15' to surface.
 Cut off casing and installed dry hole marker. Well P & A 8/31/79.
 Plugging Procedure verbally approved by Mr. John Runyon, NMOCC.

The location is presently being restored and will be ready for inspection about October 31, 1979.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jack Hammer Jack Hammer TITLE Drilling Engineer DATE 9/28/79

APPROVED BY Eddie Seay TITLE OIL & GAS INSPECTOR DATE 10/13/79

CONDITIONS OF APPROVAL, IF ANY: