

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Rustler
T. Anhy 2168
T. Salt
T. Salt 2830
T. Yates
T. 7 Rivers
T. Queen
T. Grayburg
T. San Andres 4137
T. Glorieta 5596
T. Paddock
T. Elinebry
T. Tubb 7048
T. Drinkard
T. Abo 7818
T. Wolfcamp 9169
T. Penn.
T. Cisco (Bough C)

T. Canyon
T. Strawn
T. Atoka
T. Miss
T. Devonian
T. Silurian
T. Montoya
T. Simpson
T. McKee
T. Ellenburger
T. Gr. Wash
T. Granite
T. Delaware Sand
T. Bone Springs
T. Three Brothers 9734
T. Bough B 10032
T. Bough C 10098
T. Ranger Lake 10324

Northwestern New Mexico

T. Ojo Alamo
T. Kirtland-Fruitland
T. Pictured Cliffs
T. Cliff House
T. Menefee
T. Point Lookout
T. Mancos
T. Gallup
Base Greenhorn
T. Dakota
T. Morrison
T. Todilto
T. Entrada
T. Wingate
T. Chinle
T. Permian
T. Penn. "A"
T. Penn. "B"
T. Penn. "C"
T. Penn. "D"
T. Leadville
T. Madison
T. Elbert
T. McCracken
T. Ignacio Qtzte
T. Granite

OIL OR GAS SANDS OR ZONES
No. 1, from _____ to _____
No. 2, from _____ to _____
No. 3, from _____ to _____
No. 4, from _____ to _____
No. 5, from _____ to _____
No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet
No. 4, from _____ to _____ feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	400	400	Surface Rock, Redbeds	8868	9220	352	Dolomite
400	2186	1786	Redbeds	9220	9588	368	Dolomite, Lime, Shale
2186	3024	838	Redbeds, Salt	9588	10230	642	Limestone, Shale
3024	3743	719	Anhydrite, Salt	10230	10320	90	Lime, Shale, Dolomite
3743	4261	518	Anhydrite, Lime	10320	10500	180	Limestone, Shale
4261	4560	299	Lime				
4560	4984	424	Dolomite, Anhydrite				
4984	5530	546	Dolomite, Limestone				
5530	5786	256	Dolomite, Anhydrite, Lime				
5786	6180	394	Dolomite, Anhydrite				
6180	6694	514	Dolo, Anhy, Shale, Sand				
6694	7832	1138	Dolomite, Anhydrite				
7832	8220	388	Shale				
8220	8868	648	Shale, Dolomite				