

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

PERMIT IN THEORETICAL
(Other instructions on re-
verse side)

Farm Approval
Budget Bureau No. 9-5000

5. LEASE DESIGNATION AND SERIAL NO.

MA 0108497-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal #6

9. WELL NO.

7

10. FIELD AND POOL, OR WILDCAT

Guadalupe Sandhills

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

26 775 22000 NADON

12. COUNTY OR PARISH 13. STATE

Roosevelt N.M.

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

Country Land Company

3. ADDRESS OF OPERATOR

First State Bank Bldg. Amarillo, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

5. PERMIT NO.

15. ELEVATIONS (Show whether DT, RT, CR, etc.)

4355.5' CR.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETS

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drill 3 1/4" hole to 1850'. Cement 7" casing to surface w/ 2000 lb cement plus 8% cel, tail in w/ 180 SX neat treated with 2% calce. Test casing to 1000 psi

2. Drill 3 1/4" hole to 4400' TD. Run logs, cement 4 1/2" casing at 3400' with 180 SX Incon plus 8% cel saturated salt cement. Tail in with 180 SX Incon saturated cement. Test casing to 2000 psi

3. Reperforate and stimulate for commercial production.

18. I hereby certify that the foregoing is true and correct

SIGNATURE *Edward K. Keenan*

TITLE *District Accountant*

DATE *5/25/60*

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side

APPROVED

MAY 25 1960

J. L. GUNSON
ACTING DISTRICT ENGINEER