

COUNTY **CHAVES** FIELD **Cato** STATE **NM**
 OPR **SHELL OIL COMPANY** MAP
4 **Hodges "B"** **Federal**
Sec. 34, T-8-S **R-30-E**
660' FSL, 660' FWL of Sec. CO-ORD **30-005-20224**
 Spd **2-15-68**
 Cmp **3-15-68** CLASS

CSG & SX - TUBING			FORMATION	DATUM	FORMATION	DATUM
9 5/8"	264'	150				
4 1/2"	3622'	400				

LOGS EL GR RA IND HC A
 TD 3623'; PBD 3480';
 IP San Andres Perfs 3451-75' Pmpd 35 BOPD + 118 BW. Pot. Based
 on 24 hr test, GOR TSTM, Gravity 24.4.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. **Ard Drlg. Co.** PROP DEPTH **3700'** TYPE **RT**
 DATE

F.R. 1-25-68; Elev. 4126' DF
 PD 3700' SA
 Contr. - Ard
 2-1-68 AMEND TO ADD REFERENCE NUMBER
 2-19-68 Drlg. 3284'.
 2-26-68 TD 3623', PBD 3584', swbg.
 Perf @ 3452', 3455', 3465', 3470', 3474',
 3476', 3479', 3481', 3498', 3499', 3503',
 3506', 3512', 3515' W/1 SPI
 Acid (3452-3515') 6000 gals (28%)
 Swbd 8 BO + 140 BLW in 13 hrs.

3-4-68 TD 3623', PBD 3490', swbg.
Swbd 75 BW w/tr. oil in 3 hrs (3452-3515')
Sqzd 3452-3515' W/150 sx.
Perf @ 3452', 3455', 3465', 3470', 3474',
3476', 3479', 3481' W/1 SPI
Acid (3452-81') 3000 gals (28%)
Swbd 6 BO + 152 BW in 6 hrs (3452-81')
3-11-68 TD 3623', PBD 3480', prep RUP
Sqzd 3452-81' W/150 sx.
Drld out to 3480'
Perf @ 3451', 3454', 3456', 3466', 3469',
3473', 3475' W/1 SPI
Acid (3451-75') 2000 gals (28%)
Swbd 35 BO, 62 BLW + 92 BFW in 19 hrs.
3-18-68 TD 3623', PBD 3480', WO Pot.
Ppd 35 BO + 118 BFW in 24 hrs, GOR TSTM,

Gravity 24.4.
4-1-68 TD 3623', PBD 3480', COMPLETE
LOG: Yates 1594', SA 2731', SA Marker
3285', Slaughter "A" 3435', Slaughter "B-C"
3521' (+605')