

COUNTY CHAVES FIELD Cato STATE NM 30-005-20281
 OPR EASTLAND DRILLING CO. MAP
 3 Hodges Federal
 Sec 27, T-8-S, R-30-E CO-ORD
 988' FSL, 2310' FEL of Sec.

Spd 2-19-69	CLASS		EL	
Cmp 3-20-69	FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING 8 5/8" at 374' 4 1/2" at 3561' w/250 sx				
LOGS EL GR RA IND HC A				
	TD 3580'			

TEMPORARILY ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Co. Rig PROP DEPTH 3700' TYPE
 DATE

F.R. 1-30-69; Opr's Elev. 4174' KB
 PD 3700' (San Andres)
 Contractor - Co. Rig
 2-24-69 Drlg. 2917'
 3-3-69 TD 3561'; Prep Perf
 3-10-69 TD 3561'; SD Repairs
 Perf @ 3511', 3524', 3526', 3528', 3531',
 3537', 3543', 3545' w/1 SPI
 Acid (3511-45') w/17,500 gals (3 stages)
 Swbd dry w/trace oil, did not rec load
 (3511-45')
 3-17-69 TD 3561'; WOO
 Acid (3511-45') 10,000 gals
 Swbd dry

CHAVES
EASTLAND DRILLING CO.

Cato NM Sec 27-T8S-R30E
3 Hodges Federal Page 2

~~2-24-69~~

TD 3580'; TEMPORARILY ABANDONED
Deepened from 3561' to 3580'
Acid (3561-80') w/1000 gals
Swbd 17 BLW, Swbd dry (-45 BLW) (3561-80')
LOG TOPS: San Andres 2790', Pi 3356'
COMPLETION REPORTED

3-27-69