

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.O.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
1-4409

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Fred Pool Drlg. Co.	8. Farm or Lease Name OPAL
3. Address of Operator 435 White Bldg. Roswell, .N.M. 88201	9. Well No. 1
4. Location of Well UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM East THE LINE, SECTION 33 TOWNSHIP 8-S RANGE 32-E NMPM.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4378' G.L.	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER Perforate and Acidize <input checked="" type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMEN. <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-22-80 Perforated 4229-4232 feet - 2 per foot
Acid spotted 1.5 bbls. acid @4272' Sat overnight

5-23-80 Acidized with 1500 gal. 20% NE Acid. Well went on vacuum.

5-26-80 Swabbed 1/2 day. Getting back 10 bbls fluid per hr. Estimated 10%oil.

5-27-80 Swabbing into test tanks.

5-29-80 Squeezed perforations at 4229-4232. Used 135 sx Class C Cement. Retainer set @4210'. Set 48 hrs. Cement held.

6-2-80 Perforated 4186-4193'. P.M. spotted 1.5 bbls 15% HCL Acid to clean perms.

6-3-80 Acidize 1000 15% NE Acid Formation broke @ 3000# Well did not flow bk. Swabbed bk. flush water. Formation tight; no oil.

6-4-80 Swabbed 4 hrs. recovered 3 bbls. No oil. Released pulling unit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Louis James TITLE Secretary DATE 6-6-80

APPROVED BY Jerry Sexton TITLE Dist. 1. Supv. DATE JUN 9 1980

CONDITIONS OF APPROVAL, None