

Submit 3 Copies to Appropriate District Office

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION 2040 Pacheco St. Santa Fe, NM 87505

WELL API NO. 30-005-21156
5. Indicate Type of Lease Federal STATE FEE
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Drickey Queen Sand Unit
8. Well No. 54
9. Pool name or Wildcat Caprock Queen
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4414' GL; 4425' DF; 4426' KB

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: OIL WELL GAS WELL OTHER Injection
2. Name of Operator Queen Sand Operating CO.
3. Address of Operator 13760 Noel Road, Suite 1030, LB 44 Dallas, TX 75240
4. Well Location Unit Letter P : 330' Feet From The East Line and 200' Feet From The South Line Section 15 Township 14S Range 31E NMPM Chaves County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK, TEMPORARILY ABANDON, PULL OR ALTER CASING, OTHER
SUBSEQUENT REPORT OF: REMEDIAL WORK, ALTERING CASING, COMMENCE DRILLING OPNS., PLUG AND ABANDONMENT, CASING TEST AND CEMENT JOB, OTHER: set 5 1/2" casing

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
Drilled 7 7/8" hole to 3128'. Cored from 3128-3160'. DST 3100-3160'. Drlg 3160-3220'. Logged well. Spot 350 sk "H" plug @ 3220-2307'. Dress plug to 2700'. Drilled from 2700 0° to 3312' 83.5° AZM 0.90° TVD 3097.11. TD @ 3312'.
Ran 5 1/2" 17# casing as follows:
5 1/2" 17# 3275.93'
float collar 1.00'
shoe joint 43.45'
guide shoe 1.00'
total tools & casing 3321.38'
Cemented by BJ Services w/350 sks "H" + 9/10% CO-31; flush w/24bbl wtr; plug down @ 19:10 11/16/9 WOC 24 hrs before drlg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE James L. Hull, Jr. TITLE Production Clerk DATE 7/27/00
TYPE OR PRINT NAME James L. Hull, Jr. TELEPHONE NO. 972-383-8260

(This space for State Use)
APPROVED BY TITLE DATE
CONDITIONS OF APPROVAL, IF ANY: ORIGINAL SIGNED BY DATE OCT 21 2000

Submit 3 Copies to Appropriate District Office

State of New Mexico Energy Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

DISTRICT II P.O. Drawer DD, Artesia, NM 88210

DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION 2040 Pacheco St. Santa Fe, NM 87505

WELL API NO. 30-005-21156
5. Indicate Type of Lease Federal STATE FEE
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Drickey Queen Sand Unit
8. Well No. 54
9. Pool name or Wildcat Caprock Queen
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4414' GL; 4425' DF; 4426' KB

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL GAS WELL OTHER Injection
2. Name of Operator Queen Sand Operating Co.
3. Address of Operator 13760 Noel Road, Suite 1030, LB 44 Dallas, TX 75240
4. Well Location Unit Letter P : 330' Feet From The East Line and 200' Feet From The South Line Section 15 Township 14S Range 31E NMPM Chaves County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING OTHER
SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: set surface casing

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
Spud date: 11/8/99
Drill 12 1/4" hole to 365'. Ran 8 5/8" 26# as follows:
8 5/8" 328.48'
Float collar 2.30'
Shoe joint 46.25'
Tex pattern
notched shoe 75'
Total tools & csg 377.78'
Cemented by BJ as follows:
150 sks "C"+2% CC.Circ gray water. Cement 7' from surface. Topped off with 7 yds of redi-mix. Plug held. Witnessed by Stan Mayo of BLM. WOC 24 hrs before drlg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE [Signature] TITLE Production Clerk DATE 7/27/00
TYPE OR PRINT NAME James L Hull, Jr. TELEPHONE NO 72-383-8260

(This space for State Use)
APPROVED BY [Signature] TITLE PETROLEUM DIVISION DATE
CONDITIONS OF APPROVAL, IF ANY:

CR. PAUL F. HULL OCT 8 1 2001 PETROLEUM DIVISION

52