NO. OF COPIES RECEIVED	Form C-103
DISTRIBUTION	Supersedes Old C-102 and C-103
SANTA FE NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE	
U.S.G.S.	5a. Indicate Type of Lease
LAND OFFICE	State X Fee
OPERATOR	5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
oil GAS OTHER. Injection Well	7. Unit Agreement Name No. 1 No. Caprock Queen Unit
2. Name of Operator Thunderbird Oil Corporation	8. Form of Lease Name No. Caprock Queen Unit
3. Address of Operator	9. Well No.
P. O. Box 1778, Midland, Texas 79701	Tract 27, Well No. 10
UNIT LETTER J , 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM	Caprock Queen (Lea)
THE East LINE, SECTION 7 TOWNSHIP 13-S RANGE 32-E NMPN	
15. Elevation (Show whether DF, RT, GR, etc.) 4385 GL	12. County Lea
Check Appropriate Box To Indicate Nature of Notice, Report or O	
	T REPORT OF:
	r
PERFORM REMEDIAL WORK PLUG AND ABANDON X REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JQB	
OTHER	
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	g estimated date of starting any proposed
work) SEE RULE 1103.	
9-5/8" @ 292' w/150 sx.	
5-1/2" @ 3042' w/600 sx.	
4-1/2" Liner @ 2917-3047'.	
4 200 = 200 2 0 0 0 0 0	
1. Displace hole with 2500# per 100 bbls. salt base mud.	
2. Set CIBP @ approximately 2800'.	
z. Det offi e approximaterly 2000 .	
3. Set 35' cement plug (5 sx.) on top of CIBP.	
3. Set 35' cement plug (5 sx.) on top of CIBP. 4. Cut off and pull 5-1/2" casing at approximately 1000'.	
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. 	
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. 	dry hole marker.
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. Spot 10 sx. cement plug at surface and erect 4½" regulation 	dry hole marker.
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. Spot 10 sx. cement plug at surface and erect 4½" regulation 	dry hole marker.
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. Spot 10 sx. cement plug at surface and erect 4½" regulation Clean up location for NMOCC inspection and approval. 	dry hole marker.
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. Spot 10 sx. cement plug at surface and erect 4½" regulation Clean up location for NMOCC inspection and approval. 	dry hole marker.
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. Spot 10 sx. cement plug at surface and erect 4½" regulation Clean up location for NMOCC inspection and approval. 	dry hole marker.
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. Spot 10 sx. cement plug at surface and erect 4½" regulation 	dry hole marker.
3. Set 35' cement plug (5 sx.) on top of CIBP. 4. Cut off and pull 5-1/2" casing at approximately 1000'. 5. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. 6. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. 7. Spot 10 sx. cement plug at surface and erect 4½" regulation 8. Clean up location for NMOCC inspection and approval.	dry hole marker.
 Set 35' cement plug (5 sx.) on top of CIBP. Cut off and pull 5-1/2" casing at approximately 1000'. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. Spot 10 sx. cement plug at surface and erect 4½" regulation Clean up location for NMOCC inspection and approval. 	dry hole marker.
3. Set 35' cement plug (5 sx.) on top of CIBP. 4. Cut off and pull 5-1/2" casing at approximately 1000'. 5. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. 6. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. 7. Spot 10 sx. cement plug at surface and erect 4½" regulation 8. Clean up location for NMOCC inspection and approval. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
3. Set 35' cement plug (5 sx.) on top of CIBP. 4. Cut off and pull 5-1/2" casing at approximately 1000'. 5. Spot 35 sx. cement plug in-and-out of 5-1/2" casing stub. 6. Spot 35 sx. cement plug in-and-out of 9-5/8" casing stub. 7. Spot 10 sx. cement plug at surface and erect 4½" regulation 8. Clean up location for NMOCC inspection and approval.	dry hole marker.

CONDITIONS OF APPROVAL, IF ANY: