

Orig & cc: OCC
cc: VDA

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

(Form C-103)
(Revised 7/1/52)
RECORDED
APR 15 1953
OIL CONSERVATION COMMISSION
HOBBES OFFICE

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) Perforation and acid	X

April 15, 1953
(Date)

Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company
(Company or Operator)

State #251
(Lease)

Frank Frawley Drilling Company
(Contractor)

Well No. 1 in the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 28

T. 13 S, R. 33 E, NMPM, Las J Pool, Lea County.

The Dates of this work were as follows: ~~4-11-53/6/~~ 4-9-53 set pipe - 4-12-53 Perf. - 4-14-53 acidized

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19____, and approval of the proposed plan (was) (was not) obtained. (Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 9752

Set 5 1/2" casing @ 9751 and cemented with 500 sacks - let set 72 hours and tested with 1000# for 30 minutes - No decrease in pressure - drilled cement plug to 9704.

Perforated 5 1/2" casing from 9637 to 9657 and 9664 to 9682 with four 1/2" jet shots per foot.

Ran 9693' of 2" UE tubing, swabbed well in and it flowed 274 Bbl. of new oil in 18 hours natural.

Acidized with 2,000 gallons of 15% low tension acid by Dowell Inc., thru casing perforations 9637 to 9657 and 9664 to 9682, flowed 180 Bbl. of new oil in 7 hours. last 3 hours @ 68 Barrel per hour.

Witnessed by Harold W. Shaner
(Name)

Sinclair Oil & Gas Co.
(Company)

Foreman
(Title)

Approved: OIL CONSERVATION COMMISSION

Ray Yumbro
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name W. Satter

Position Dist. Supt.

Representing Sinclair Oil & Gas Company

Address Box 1927 Hobbs, N.M.

(Title)

(Date)

APR 17 1953