NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Notice by Checkin	g Below	
Notice of Intention to Change Plans	Notice of Intention to Temporarily Abandon Well	Notice of Intention to Drill Deeper	
Votice of Intention to Plug Well	Notice of Intention to Plug Back	Notice of Intention to Set Liner	
Notice of Intention o Squeeze	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)	
Notice of Intention o Gun Perforate	Notice of Intention (Other)	Notice of Intention (Other)	
DIL CONSERVATION COMMIS	SION Lovington, New Mexico	March 1, 1961 (Date)	
Gentlemen:	(Flace)	(Date)	
Following is a Notice of Intent	ion to do certain work as described below at the		
Amerada Petroleum C	rporation J. E. Stevens		•
(Company o	or Operator) 		(Unit)
_	_	1. 1/1.,	
Loa			
(F	FULL DETAILS OF PROPOSED PLATOLLOW INSTRUCTIONS IN THE RULES AT		
	flow valves, rerun tubing packe		
	.m 091/1 += 0001 005/1 += 00601		L DACIO
- 41144 441411 114	m 98141 to 98231, 98541 to 98681	, 9882 to 9896, 9936	to 9954°
	om 9814' to 9823', 9854' to 9868'		
with 3000 Cal 15		sealers injected constant	l y
with 3000 Gal 15	Reg Acid using 250 Rubber Ball	sealers injected constant	l y
with 3000 Gal 15	Reg Acid using 250 Rubber Ball	sealers injected constant	l y
with 3000 Gal 15	Reg Acid using 250 Rubber Ball	sealers injected constant	l y
with 3000 Gal 15	Reg Acid using 250 Rubber Ball	sealers injected constant	l y
with 3000 Gal 15	Reg Acid using 250 Rubber Ball	sealers injected constant	l y
with 3000 Gal 15 during treatment valves and resum	Reg Acid using 250 Rubber Ball Pull tubing packer and Ecldow producing.	sealers injected constant	l y
with 3000 Gal 15	Reg Acid using 250 Rubber Ball Pull tubing packer and Ecldow producing.	sealers injected constant	l y
with 3000 Gal 15 during treatment valves and resum	Reg Acid using 250 Rubber Ball Pull tubing packer and Ecldow producing.	sealers injected constant	l y

Title.....

Name........ Box. 636, Lovington, New Mexico