

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other instruction:
verse side)TB*
re-Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen on a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. BM 06171-A
2. NAME OF OPERATOR Champlin Petroleum Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 1797, Midland, Texas		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' PSL & 660' PSL, Section 6, T-14-S, R-33-E, Lea County, New Mexico		8. LEASE OR LEASE NAME Matheson Federal
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4276' DF		10. FIELD AND POOL, OR WILDCAT Wolfcamp
		11. SEC., T., R., S., AND SURVEY OR BLM. MAP NO. Sec 6, T-14-S, R-33-E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	RETAINING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☒	ABANDONMENT* ☐
(Other) ☐	

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log Form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On May 24, 1966, operations began to change the pumping equipment on this well from hydraulic to a beam type unit. After recovering the hydraulic pump, the well was reperforated 2 shots per foot from 9936' to 9946' and acidized with perforations with 1,000 gallons Super "X" 28% H.S. Acid with 2 gallons W-25 emulsion breaker and 1,000 gallons fresh water mixed with 1 gallon W-25 emulsion breaker. The tubing, bottom hole pump and rods were then run for completion. A 24 hour test on June 16, 1966 pumped 57 barrels oil and 134 barrels water with a Gas-Oil Ratio of 1,109 cu. ft./bbl.

18. I hereby certify that the foregoing is true and correct

SIGNED H. H. Brown H. H. Brown TITLE District SuperintendentDATE 6-17-66

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

District Engineer

Instructions

General: This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations and if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations of Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud, or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing; and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1985-O-688229

6-7-85