

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUL 5 8 07 AM '66

Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.
-

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name -
2. Name of Operator Ashmun & Hilliard	8. Farm or Lease Name Clarence Church
3. Address of Operator 710 Vaughn Building, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER "P" 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 17 TOWNSHIP 13-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4159' GL	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Commencing June 25, 1966, at 5:00 a.m., operator directed the plugging and abandonment as follows:

Shot off and pulled 1280' of 8 5/8" casing. Placed cement plugs as follows:

- 50' 25 sx plug at TD 10,840'
- 50' 25 sx plug at top of Wolfcamp limestone 9,460'
- 50' 25 sx plug at top of Abo 7,820'
- 50' 25 sx plug at top of Drinkard 7,060'
- 50' 25 sx plug at top of Glorieta 5,660'
- 50' 25 sx plug at top of San Andres 4,200'
- 50' 25 sx plug in top of stub of 8 5/8" casing 1,280'
- 50' 25 sx plug in base of surface 11 3/4" casing 337'
- 30' 10 sx plug in top of surface 11 3/4" casing

Applied mud by pump between all cement plugs from TD back to surface. Surface marker set in top of cement. P & A operations completed at 7:30 a.m. on June 26, 1966. Left 2909' 8 5/8" casing in hole and 333' of 11 3/4" surface casing in hole.

Authorization to plug and abandon given by Eric Engbrecht in person on June 17, 1966. Notification will be given when site is ready to be inspected.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jim West TITLE Production Superintendent DATE June 27, 1966

APPROVED BY John W. Runyan TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: