

MAR 5 1970
 Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
 State Fee
 5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER
 2. Name of Operator: **An-Son Corporation**
 3. Address of Operator: **3814 North Santa Fe, Oklahoma City, Oklahoma**
 4. Location of Well: UNIT LETTER **E**, **2361** FEET FROM THE **North** LINE AND **330** FEET FROM THE **West** LINE, SECTION **1** TOWNSHIP **14S** RANGE **37E** NMPM.
 7. Unit Agreement Name
 8. Farm or Lease Name: **McCrary**
 9. Well No.: **1**
 10. Field and Pool, or Wildcat: **King Pennsylvania**
 15. Elevation (Show whether DF, RT, GR, etc.): **GR 3836.7**
 12. County: **Lea**

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER _____	<input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We propose to plug and abandon above subject well to specifications set forth by the Conservation Commission or as follows:

Producing strata will be cement plugged (50 sacks) prior to shooting and pulling production string. A cement plug (50 sacks) will be pumped to the base of the surface casing as the production string is pulled. A 15 to 25 sack cement plug will be placed in the top of the surface casing prior to welding a steel plate over the top of the surface casing.

Handwritten notes:
 25 sacks @ 2 1/2" - 1 1/2" - 1 1/2"
 25 " @ 2 1/2" - 1 1/2" - 1 1/2"
 25 " @ 2 1/2" - 1 1/2" - 1 1/2"
 25 " @ 2 1/2" - 1 1/2" - 1 1/2"
 25 " @ 2 1/2" - 1 1/2" - 1 1/2"
 15 " cap

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: [Signature] TITLE: Production Manager DATE: March 2, 1970
 APPROVED BY: [Signature] TITLE: SECRETARY DATE: 70
 CONDITIONS OF APPROVAL, IF ANY: