		, and ,	7		
NO. OF COPIES RECEIVED			). Form C-10:	2	
DISTRIBUTION	<del></del>			Supersedes Old	
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION		_	C-102 and C-103	
	NEW MEXICO OIL CON	ISERVATION COMMISSION	Effective	l <b>-1-6</b> 5	
FILE			Sa Indicate Ti	upe of League	
U.S.G.S		[	State Fee X		
LAND OFFICE		State	5. State Oil & Gas Lease No.		
OPERATOR		*	5. State Oil &	Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)					
1. OIL X GAS WELL X			7. Unit Agreen	nent Name	
2. Name of Operator	OTHER-		8. Form or Lea	ise Name	
Union Oil Company of California			Owens	Owens	
3. Address of Operator			9. Well No.		
P. O. Box 671 - Midland, Texas 79702			2	2	
4. Location of WellSurf. I 2310 990			10. Field and	10. Field and Pool, or Wildcat	
	583.33 FEET FROM THE Sout	- ·	Morton W	olfcamp East	
UNIT LETTER	FEET FROM THE	LINE AND FEE	TITITI MON	minim	
THE East LINE, SECTION	on 34 TOWNSHIP 14 S	outh RANGE 35 East	NMPM.		
	15. Elevation (Show whether	r DF, RT, GR, etc.)	12. County		
	4001	.8' GR.	Lea		
TEMPORARILY ABANDON  PULL CR ALTER CASING  OTHER	CHANGE PLANS	COMMENCE DRILLING OPNS.  CASING TEST AND CEMENT JOB  OTHER	PLU	G AND ABANDONMENT	
17. Describe Proposed or Completed Opwork) 5EE RULE 1103.	erations (Clearly state all pertinent de	etails, and give pertinent dates, inc	luding estimated date of	of starting any propose	
11- 9-77 - Moved in and 11-10-77 - Set C.I. Brid cement 10,71	dge Plug at 10,750', du	ng unit. Pulled rod mped 3 sx cement on	s, pump, and t top of C.I.B.P	ubing.	
11-11-77 - Cut 5-1/2" O	D Casing at 3,800', cou		ree. Ran free	-point,	
11-13-77 - Cut 5-1/2" 05 5-1/2" OD 17- Casing and 8- 11-14-77 - Shot 8-5/8" 6 8-5/8" OD Cas	# N-80 Casing. Ran 2" -5/8" OD Casing from 2,	led and laid down 70 tubing to 2,300', spo 300' to 1,950' with ald not pull casing	otted Plug No. 100 sx Class " free. Ran fre	2 in 5-1/2" C" neat cemen e-point, shot	
bottom of 11 No. 5 in top 9.5# mud plad installed 4"	g to 810', spotted Plug 705' with 80 sx cement -3/4" OD Casing from 45 of 11-3/4" OD Casing f ced between plugs. Wel x 4' pipe with dry hol AND ABANDONED NOVEMBER	. Spotted Plug No. 60' to 320' with 120 from 30' to surface wided 1/2" steel plate e marker.	4 in 11" open sx cement. Sp ith 20 sx ceme	hole and otted Plug nt.	
16.1 bereby certify that the information	J.R. Hughes	of my knowledge and belief. strict Drilling Supt	. DATE Feb	ruary 3, 1977	

OLL & GAS INSPECTOR

AUG

, 19/8