

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
IG-4456	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Adobe Oil & Gas Corporation		8. Farm or Lease Name State "4"
3. Address of Operator 1100 Western United Life Bldg., Midland, TX 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>E</u> , <u>1980</u> FEET FROM THE <u>north</u> LINE AND <u>660</u> FEET FROM THE <u>west</u> LINE, SECTION <u>4</u> TOWNSHIP <u>13-S</u> RANGE <u>36-E</u> NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3997 GL		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole @ 11:30 a.m. 8/1/79. Set 382' of 13-3/8" 61# K-55 csg @ 380' KB & cemented w/420 sx Class "C" cement w/1/4# flocele/sx w/2% CaCl. Cement circ. POB 12:15 a.m. 8/2/79. Cut off, nipple up & tested BOP, head & csg to 1000# for 30 min, ok. Drld 11" hole to 4590' & ran 109 jts 32#, 28#, 24# 8-5/8" K-55 csg & set @ 4589'. Cemented w/1700 sx Howco Lite w/10# salt w/1/4# flocele w/3# Gilsonite/sx + 200 sx Class "C" w/2% CaCl. Cement circ. POB 6 a.m. 8/9/79. Cut off, nipple up & tested BOP, head & csg to 2000#, ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bill Owens TITLE Engineer DATE 10/3/79

APPROVED BY Jerry Sexton TITLE Dist. 1. Supv. DATE OCT - 9 1979

CONDITIONS OF APPROVAL, IF ANY: