

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
Rustler	1764		
T. Anhy		T. Ojo Alamo	T. Penn. "B"
T. Salt	2562	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	2680	T. Pictured Cliffs	T. Penn. "D"
T. Yates		T. Cliff House	T. Leadville
T. 7 Rivers		T. Menefee	T. Madison
T. Queen	3440	T. Point Lookout	T. Elbert
T. Grayburg		T. Mancos	T. McCracken
T. San Andres	4158	T. Gallup	T. Ignacio Qtzte
T. Glorieta	5602	T. McKee	T. Granite
T. Paddock		Base Greenhorn	
T. Blinbry		T. Dakota	
T. Tubb	7030	T. Morrison	
T. Drinkard		T. Todilto	
T. Abo	7762	T. Entrada	
T. Wolfcamp Ls	9172	T. Wingate	
T. Penn.		T. Chinle	
T. Cisco (Bough C)		T. Permian	
		T. Penn. "A"	
T. Canyon			
T. Strawn			
T. Atoka			
T. Miss			
T. Devonian			
T. Silurian			
T. Montoya			
T. Simpson			
T. XX Marker	9380		
T. Virgilian	9770		

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.	
No. 2, from.....to.....feet.	
No. 3, from.....to.....feet.	
No. 4, from.....to.....feet.	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	85	85	Surface, Sand, Red Rock	5580	6140	560	Dolomite, Lime, Sd, Anhy.
85	1166	1081	Redbeds	6140	6400	260	Anhy, Dolo, Shale, Sand
1166	3404	2238	Redbeds, Anhydrite	6400	7080	680	Anhy, Dolomite, Shale
3404	3546	142	Sand, Anhydrite, Shale	7080	7740	660	Dolo, Anhy, Sand, Shale
3546	3779	233	Anhydrite, Redbeds	7740	9000	1260	Dolo, Anhydrite, Shale
3779	4200	421	Anhydrite, Shale	9000	9360	360	Dolomite, Shale, Lime
4200	4260	60	Dolo, Anhydrite, Shale	9360	9780	420	Chert, Lime, Shale
4260	4700	440	Dolomite	9780	10185	405	Lime
4700	4780	80	Dolomite, Sand, Anhydrite				
4780	5000	220	Dolomite				
5000	5120	120	Dolomite, Anhydrite				
5120	5480	360	Dolomite, Lime, Chert Anhy				
5480	5580	100	Dolomite, Lime				

RECEIVED

JAN 10 1985

**O.C.D.
HOBBS OFFICE**