

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Cavalcade Oil Corporation	8. Farm or Lease Name Goldengate
3. Address of Operator P.O. Box 16187, Lubbock, TX 79490	9. Well No. 1-Y
4. Location of Well UNIT LETTER <u>E</u> <u>2030</u> FEET FROM THE <u>North</u> LINE AND <u>635</u> FEET FROM THE <u>West</u> LINE, SECTION <u>18</u> TOWNSHIP <u>12S</u> RANGE <u>38E</u> <u>NSMPM.</u>	10. Field and Pool, or Wildcat Gladiola - Wolfcamp
15. Elevation (Show whether DF, RT, GR, etc.) 3872 GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/27/85 Set 362' of 13 3/8", 62# casing, circulated 195 sx. cement at surface. Total cement used - 350 sx. Class "C" w/2% CaCl₂. Float held 500# for 15 minutes.

5/3/85 Set 4445' of 8 5/8", 32# & 24# casing, circulated 300 sx. cement at surface. Total cement used - 1250 sx. Halliburton Lite followed by 300 sx. Class "C" Float held 1000# for 15 minutes.

5/19/85 Set 9792' of 5 1/2", 17# casing. Total cement used - 400 sx. Class "H"/50-50 Poz + 5#/sx. salt + .5% CFR-2. Float held 1000# for 30 minutes.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Randall Egan TITLE Vice President - Land DATE 6/20/85

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____ TITLE _____ DATE JUL - 1 1985

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 28 1985

0213
HOBBS OFFICE