

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-34100
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No. NA
7. Lease Name or Unit Agreement Name Hodge
8. Well No. 1
9. Pool name or Wildcat Wildcat Devonian

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Charles B. Gillespie, Jr.	
3. Address of Operator P.O. Box 8 Midland, Texas 79702	
4. Well Location Unit Letter M : 495 Feet From The South Line and 495 Feet From The West Line Section 27 Township 12S Range 38E NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3807' GR, 3823' KB	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

09/27/97 Drilled 12-1/4" hole to 2694', drilled 11" hole to 4510'. Ran 8-5/8" 32# J-55 & S-80 csg to 4509' & cemented w/1200 sacks 50/50 Pox A with 5# salt/sack, 1/4" Flocele/sack, followed by 200 sacks class "C" w/2% CaCl. Circulate 150 sacks cement. Bumped plug to 2000 psi. Float held. WOC 8 hrs. Set slips, cut off casing. NUWH & RIH w/7-7/8" bit. Test casing & BOP to 2500 psi. Commence drill out.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mark Mladenka TITLE Production Manager DATE 9/30/97  
TYPE OR PRINT NAME Mark Mladenka TELEPHONE (505) 683-1765

(This space for State Use) ORIGINAL SIGNED BY CHRIS WILLIAMS  
DISTRICT I SUPERVISOR

OCT 10 1997

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: