

12/21/81

Memo

From

LES CLEMENTS
Oil & Gas Inspector

P & A -

To Les to Herndley.

Mosley Pet. - S.N. m 36 #1 990/6 - 1650/5

36-6-33 -

PBTD. on str.

133/8 @ 410- Cnt

97/8 @ 3179. Cnt

4 1/2 @ 8300-1590' ^{DP-TC}

Proffo: 8016-8161'

TC @ 7755' in cut of Cq. & Tcd. lugs.

Top of 7721' -

~~Set~~ Prof 7650-59

Spent 50 ft at 7650 & tag @ 7093'

Prof @ 4947-65' -

BPC @ 4965 w/ 35' -

← Already Done

Set CIBP @ 4800' + 35' cmt.

(new work)

Drop to mud.

Top of salt 1930' to 50' over cut to 1350'

(Cut 4 1/2 @ 1400' Cmt Top of salt to 50' above)

Steel.

10 ft w/ markers

It may decide not to cut & pull 4 1/2" in that
Case set 100' plug inside 4 1/2" @ top of salt.

@ 1930' Oil Conservation Division

Hobbs, New Mexico

& then 10 ft w/ markers.



Petroleum Information.

© Copyrighted Reproduction Prohibited

COUNTY	ROOSEVELT	FIELD	Wildcat	STATE	NM
DPR	MOSELEY PETROLEUM CORP.			API	30-041-20612
NO	1	LEASE	State "36"	MAP	
	Sec 36, T6S, R33E			COORD	2-1-50 NM
	1650 FSL, 990 FEL of Sec			SPD	8-22-81
	16 mi SE/Elida			CMP	12-23-81
CSG	9 5/8-460-410 sx				
	4 1/2-8300-2600 sx				
			WELL CLASS: INIT WF FIN WF LSE. CODE		
			FORMATION	DATUM	FORMATION
			ID 8301 (ELBG)	PBI	

DRY & ABANDONED

CONTR	Republic #6	OPRSLEV	4345 GL	sub-s 13
-------	-------------	---------	---------	----------

9-14-81 F.R. 8-17-81
 9-1-81 PD 9000 RT (Ellenburger)
 9-7-81 AMEND OPERATOR: Formerly reported as Eastland
 9-15-81 Oil Co., The
 10-5-81 Tight
 10-12-81 Drlg 3276 "Tight"
 10-19-81 TD 3276; fsg
 10-29-81 Drlg 6197
 2-1-82 Drlg 7834
 2-6-82 Drlg 8125
 TD 8301; "Tight"
 TD 8301; Dry & Abandoned
 Completion work "Tight"
 COMPLETION ISSUED

2-1-50 NM
 IC 30-041-70048-81