Form 3 160-5

UNITED STATES

N.M. Oll Cons. Division 1625 N. French Dr.

Hobbs,	NMdg 5240 1004-0135
1 -	F Marcal 2 1 1002

	Expires: March 3 1,1993
BUREAU OF LAND MANAGEMENT	5. Lease Designation and Serial No.
	LC 029509A
SUNDRY NOTICES AND REPORTS ON WELLS	6. If Indian, Allottee or Tribe Name
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.	
Use "APPLICATION FOR PERMIT—" for such proposals	
SUBMIT IN TRIPLICA TE	7. If Unit or CA, Agreement Designation
1. Type of Well	
Well Gas Other	8. Well Name and No.
2. Name of Operator	MCA Unit #37
Conoco Inc	9. API Well No.
3. Address and Telephone No.	30-025-00633
10 DESTA DR. STE. 100W, MIDLAND, TX 79705-4500 (915) 686-5580	10. Field and Pool, or Exploratory Area
4 Location of Well (Footage, Sec., T. R. M. or Survey Description)	Maljamar Grayburg/SA
ACCOUNTY O ACCOUNTY OF THE PACE OF	11. County or Parish, State
1980' FNL & 1980' FEL, Sec. 22, T17S, R32E, G	
	Lea, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
Notice of Intent Abandonment	Change of Plans
Recompletion	New Construction
Subsequent Report Plugging Back	Non-Routine Fracturing
Casing Repair	Water Shut-Off
Final Abandonment Notice Altering Casing	Conversion to Injection
	Dispose Water
	Dispose Water Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

The subject well was P&A'd as of 5/15/02, per the attached procedure.



PETROLEUM ENGINEER	
Reesa R. Wilkes	
Title Regulatory Specialist	Date5/21/02
(This space for Federal or State office use)	
Title	Date
D, FILE ROOM	
gly and willfully to make to any department or agency of the	United States any false, fictitious or fraudulent statement
	Reesa R. Wilkes Title Regulatory Specialist Title D, FILE ROOM

Daily Activity Report

Conoco Inc. MCA Unit #37 Lea County, New Mexico

Job #3704

04/17/02 Notified BLM, Kathy Haston, Steve Caffey & Deg Alans. MI rig and plugging equipment. NU BOP. Tagged retainer set @ 2,975'. Circulate hole w/ mud and stung into retainer, unable to establish rate @ 1,500 psi. Pumped 25 sx C cmt 2,975 – 2,830'. Pumped 25 sx C cmt 2,046 – 1,901'. Perforated csg @ 1,030'. Pressured up to 1,300 psi and established circulation in 7" x 8-5/8" annulus. Squeezed 75 sx C cmt 1,030 – 850'. SDFN.

04/18/02 Notified BLM, Pat. Tagged cmt @ 855'. Perforated csg @ 50' and squeezed 15 sx C cmt 50' to surface.

05/15/02 Cut off wellhead and installed marker. Backfilled pit and cellar, removed anchors.