

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
**B-10137**

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>P &amp; A</b>	7. Unit Agreement Name
2. Name of Operator <b>Atlantic Richfield Company</b>	8. Farm or Lease Name <b>State 245</b>
3. Address of Operator <b>P. O. Box 1978, Roswell, New Mexico 88201</b>	9. Well No. <b>2</b>
4. Location of Well UNIT LETTER <b>B</b> <b>990</b> FEET FROM THE <b>North</b> LINE AND <b>1650</b> FEET FROM THE <b>East</b> LINE, SECTION <b>28</b> TOWNSHIP <b>13-S</b> RANGE <b>33-E</b> NMPM.	10. Field and Pool, or Wildcat <b>Lazy J-Penn.</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4246' GR</b>	12. County <b>Ica</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has been plugged and abandoned in the following manner. Set 5½" CIBP @ 9560' and capped w/2 sx cement. Shot off 5½" csg at 5750'. Recovered 158 jts (5565.47') of 5½" casing. Spotted 30 sk cement plug 5540-5680; 30 sk cement plug 5309-5432; 30 sk cement plug 3934-4042'; 30 sk cement plug 302-340; 10 sk cement plug in top of 13-3/8" casing. 9#/gal gel mud was used to spot all plugs. Erected dry hole marker. 8-5/8" and 13-3/8" casing strings remain intact. 8-5/8" stub from original P&A is at 320' and 13-3/8" shoe at 322'.

**Well P&A 4/3/71.**

Your office will be notified when location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *A. D. Sritches* TITLE District Drilling Supervisor DATE 4/12/71

APPROVED *Nathan E. Clegg* TITLE OIL & GAS INSPECTOR DATE JUN 19 1972

CONDITIONS OF APPROVAL, IF ANY: