

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION

APR 21 9 39 AM '69

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee

5. State Oil & Gas Lease No.
B9642

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name -
2. Name of Operator Phillips Petroleum Company	8. Farm or Lease Name Chem State
3. Address of Operator Room B-2, Phillips Bldg., Odessa, Texas 79760	9. Well No. 4
4. Location of Well UNIT LETTER I , 660 FEET FROM THE East LINE AND 1980 FEET FROM THE South LINE, SECTION 4 TOWNSHIP 15-S RANGE 32-E NMPM.	10. Field and Pool, or Wildcat Tulk (Wolfcamp)
15. Elevation (Show whether DF, RT, GR, etc.) 4303' Gr., 4319' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MI and RU Cactus Drlg. Company rig. Spudded 17 1/2" hole at 5 PM, 4-5-69. Drilled to 396' set 13 joints 13-3/8" OD 48# H-40 casing (396') at 396' on 4-6-69. Howco cemented with 500 sx. Class H w/2% CaCl2 in first 300 sx w/1/2# Floseal/sx. Plug to 260'. Circulated 70 sx. WOC 18 hrs, tested casing w/800# for 30 minutes, OK. Drilled cement 260' to 396', started drilling ahead in 11" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Associate Reservoir Engineer DATE April 17, 1969

APPROVED BY [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: