

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Freeport Oil Company	7. Unit Agreement Name
3. Address of Operator 1005 V & J Tower, Midland, Texas 79701	8. Farm or Lease Name West Garrett-State
4. Location of Well UNIT LETTER M 990 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 16S RANGE 38E NMPM.	9. Well No. 1 10. Field and Pool, or Wildcat West Garrett-Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3730' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASINGS <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well was plugged and abandoned October 5, 1970, with Class "H" cement. Plugs were set as follows:

25 Sxs.	Total Depth	12,350-12,272'
25 Sxs	Top of Morrow	11,640-11,572'
25 Sxs.	Top of Penn	10,860-10,782'
25 Sxs.	Top of Wolfcamp	9,380- 9,302'
25 Sxs.	Top of Abo	8,610- 8,523'
25 Sxs.	Top of Glorieta	6,550- 6,464'
25 Sxs.	Bottom of 8-5/8" csg.	5,200- 5,120'
25 Sxs.	8-5/8" csg. stub	143- 109'
10 Sxs.	Surface	Surface

Monument was set.

Left 10 jts. of 13-3/8" casing set at 403' cemented with 400 sxs. and 146 jts. of 8-5/8" casing set at 5,200' cemented with 500 sxs. in the hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Don Sparks TITLE Division Engineer DATE 10/14/70

APPROVED BY Joe D. Ramsey TITLE _____ DATE SEP 6 1970
CONDITIONS OF APPROVAL, IF ANY: Dist. 1, Supv.

FRONT COVER

1960-1961

OIL CONSERVATION BOARD

STUDY 2

