

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.
LC-029405(b)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐
2. NAME OF OPERATOR **Continental Oil Company**
3. ADDRESS OF OPERATOR **Box 460, Hobbs, N.M. 88240**
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME
MCA
8. FARM OR LEASE NAME
MCA UNIT 1
9. WELL NO.
283
10. FIELD AND POOL, OR WILDCAT
MALJ G-SA Repress
11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

14. PERMIT NO.
2565' FSL + 1295' FEL of Sec 19
15. ELEVATIONS (Show whether DF, RT, CR, etc.)
3955'

12. COUNTY OR PARISH
LEA
13. STATE
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) **Repair Surface Waterflow** ☒
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

WORK STARTED: 10-20-76 WORK COMPLETED: 10-29-76
WORK DONE: PULLED RODS, PUMP & TBG. SET RBP AT 3500' & CAPPED
W/3 SKS SAND. LOCATED WTR ENTRY, 2300'-2400' W/SOUND LOG. PERF
5-1/2" CSG, 2370'-72' W/2 JSPP. LOCATED & REPAIRED HOLE IN
8-5/8" - 5-1/2" ANNULUS W/900 SKS THINSET & 300 SKS CLASS "C"
CMT, 4% CA CL. RAN TRACER. FOUND CMT TO 925'. FMPD 100 BELS
BRINE, 2 BFM & 100 BELS HOWCO SPECIAL GELLING AGENT AT 30 BFM W/
1800#. SQUEEZED PERFS AT 2370'-72' W/200 SKS THINSET & 50 SKS
CLASS "C" CMT, 4% CA CL. DISPLACED CMT TO 2295' W/FW AT 1 BFM
W/1100#. DO CMT TO 2372'. TESTED TO 500# - OK. DO CMT &
WASHED SAND OFF RBP. RAN POTENTIAL LOG. PULLED RBP. RAN TBG,
RODS & PUMP. P.O.P.
LOCATION: 2565' FSL & 1295' FEL OF SECTION 19, T-175, R-32E

18. I hereby certify that the foregoing is true and correct.

SIGNED

Wm. A. Hatterfield

TITLE **Admin. Serv.**

DATE **5-19-77**

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 20 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

USGS (5) MCA 4, File

RECEIVED

MAY 24 1977

U.S. DEPARTMENT OF COMMERCE
WASHINGTON, D.C.