

Copy to DC

COPY TO D. C. G.

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other PLA

2. NAME OF OPERATOR  
Conoco Inc.

3. ADDRESS OF OPERATOR  
P.O. Box 460 Hobbs N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1225' FNL & 1295' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

5. LEASE  
LC-061841

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
MCA

8. FARM OR LEASE NAME  
MCA Unit

9. WELL NO.  
342

10. FIELD OR WILDCAT NAME  
Maljamar G-5A

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 26, T-17S, R-32E

12. COUNTY OR PARISH | 13. STATE  
Lea | N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3975' GR

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF
- FRACTURE TREAT
- SHOOT OR ACIDIZE
- REPAIR WELL
- PULL OR ALTER CASING
- MULTIPLE COMPLETE
- CHANGE ZONES
- ABANDON\*
- (other) Re-enter & PLA

- 
- 
- 
- 
- 
- 
- 
- 
- 

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

FEB 12 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

MIRU 2-1-80. Drilled out 30' cmt. @ surface.

Drilled on cmt. plug from 900' to 930'. Drill retainer @ 2125'-2155'.

Spot 20-sack class "C" cmt. plug from 2150' to 2000'. Spot 15 sk.

Class "C" cmt. from 1150' to 1000'. Perf. @ 900' & again @ 870' w/ 2

JSPF. Could not pmp. into perfs. Perf @ 500' w/ 2 JSPF. Able to estab.

circ. Pumped 160 sk. class "C" cmt. w/ additives dn. 5 1/2" csg. Circ.

40 sk. cmt. to pit from csg.-csg. annulus. Erect dry hole marke

& clean location 2/7/80

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm A. Butcher TITLE Admin. Supervisor DATE 2/8/80

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

USGS-5  
MCA-4  
FILE

APPROVED

MAY 2 1980

ACTING DISTRICT ENGINEER

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

See Instructions on Reverse Side