

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

U.S. GOVERNMENT PRINTING OFFICE
SUBMIT IN TRIPlicate
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0437592

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brinson Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Maljamar GB-SA

11. SEC., T., E., M., OR BLK. AND
SUEVLY OR AREA

Sec. 31, T16S, R32E

12. COUNTY OR PARISH

Lea

NM

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Tejas Oil Operators

3. ADDRESS OF OPERATOR

c/o Oil Reports & Gas Services, P. O. Box 763, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

(See also space 17 below.)
At surface

1980' FNL & 660' FEL of Sec. 31

14. PERMIT NO.

15. ELEVATIONS (Show whether FT., YD., OR, etc.)

4142.4 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PUT IN OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 8 PM 4/6/81. Cemented 8 5/8" 24# H-40 casing at 354' with 175 sacks class C 2% calcium chloride. Circulated 25 sacks. Plug down 3:30 PM 4/7/81. WOC 24 hours, tested casing with 500# for 30 minutes, test O.K.

Cemented 4 1/2" 10.5# J-55 casing at 3989 with 400 sacks lite cement, 14# salt, 3/10 of 1% halad 4, 1/4# flocele per sack, and 200 sacks class C, 1/4# flocele, 8# salt per sack, 5/10 of 1% CFR-2, 3/10 of 1% halad 9. Circulated 75 sacks. Plug down 4/25/81.

18. I hereby certify that the foregoing is true and correct

SIGNED *David R. Glass*

TITLE Agent

DATE 12/16/82

(This space for Federal Agency Use)

APPROVED BY (CEN. SEC.) DAVID R. GLASS

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JAN 12 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO