

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	TRUE VERTICAL DEPTH FEET	VERTICAL SECTION FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DOG LEG SEVERITY DG/100FT
3000.	0 30	N 15 W	2999.89	-21.97	7.28 N	21.28 W 0.28
3100.	0 30	N 15 W	3099.88	-22.29	8.13 N	21.50 W 0.00
3200.	0 45	N 16 W	3199.88	-22.70	9.18 N	21.79 W 0.25
3300.	0 45	N 10 E	3299.87	-22.92	10.47 N	21.86 W 0.34
3400.	0 45	N 10 E	3399.86	-22.84	11.76 N	21.63 W 0.00
3500.	0 45	N 2 W	3499.85	-22.90	13.07 N	21.54 W 0.16
3600.	0 45	N 18 E	3599.84	-22.87	14.36 N	21.36 W 0.26
3700.	0 45	N 14 E	3699.83	-22.65	15.61 N	21.00 W 0.05
3800.	0 45	N 18 E	3799.82	-22.44	16.87 N	20.64 W 0.05
3900.	1 15	N 11 E	3899.81	-22.20	18.56 N	20.20 W 0.51
4000.	1 30	N 14 E	3999.78	-21.95	20.90 N	19.69 W 0.26
4100.	1 0	N 4 W	4099.76	-22.01	23.07 N	19.50 W 0.63
4200.	1 0	N 19 W	4199.74	-22.55	24.77 N	19.84 W 0.26
4300.	0 45	N 14 E	4299.73	-22.79	26.27 N	19.91 W 0.55
4400.	0 45	N 7 E	4399.72	-22.70	27.56 N	19.67 W 0.09
4500.	0 30	N 16 W	4499.71	-22.91	28.64 N	19.76 W 0.35
4600.	0 15	N 16 W	4599.71	-23.16	29.27 N	19.94 W 0.25
4700.	0 30	N 27 W	4699.71	-23.47	29.88 N	20.18 W 0.26
4800.	0 30	N 21 W	4799.71	-23.91	30.68 N	20.53 W 0.05
4900.	0 45	N 7 E	4899.70	-24.17	31.75 N	20.66 W 0.39
5000.	0 30	N 28 W	4999.69	-24.48	32.80 N	20.86 W 0.45
5100.	1 0	N 24 W	5099.69	-25.19	33.98 N	21.43 W 0.50
5200.	0 45	N 13 W	5199.67	-25.83	35.42 N	21.91 W 0.30
5300.	0 45	N 41 W	5299.67	-26.55	36.58 N	22.50 W 0.36
5400.	0 30	N 67 W	5399.66	-27.49	37.21 N	23.38 W 0.37
5500.	0 30	N 15 W	5499.66	-28.11	37.85 N	23.93 W 0.44
5600.	0 45	N 66 W	5599.65	-28.88	38.65 N	24.61 W 0.58
5700.	0 45	N 23 W	5699.64	-29.88	39.56 N	25.51 W 0.55
5800.	0 45	N 23 W	5799.63	-30.52	40.77 N	26.02 W 0.00
5900.	1 0	N 27 W	5899.62	-31.32	42.15 N	26.67 W 0.26