

State of New Mexico
Energy, Minerals and Natural Resources

DISTRICT I
1825 N. French Dr., Hobbs NM 88240
DISTRICT II
1301 W. Grand Avenue, Artesia NM 88210
DISTRICT III
1000 Rio Brazos Rd., Aztec NM 87410
DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31272
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-3273
7. Lease Name or Unit Agreement Name Eidson Ranch AQB State
8. Well No. 2
9. Pool Name or Wildcat Wildcat Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well Gas Well Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South 4th Str., Artesia, NM 88210

4. Well Location
Unit Letter Q : 2080 feet from the South line and 660 feet from the East line
Section 5 Township 16S Range 33E NMPM County Lea

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4218' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <u>Re-Entry Operations</u>	<input checked="" type="checkbox"/>

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

10-14-02 Spudded on surface. TIH w/7-7/8" slip joint, 5-1/2" 17# casing. Tagged stub @ 2805'. Cemented w/100 sx BJ Lite, 50 sx C Neat w/additives. TIH w/5-1/2" cement retainer and set @ 5683'. Mixed and pumped 300 sx C Neat w/additives. Squeezed to 1600#. Drilled and cleaned out to 5890'. TIH w/5-1/2" cement retainer and set @ 5673'. Squeezed w/100 sx C Neat w/additives. Drilled and cleaned out to 10900'. Set RBP @ 10900'. Spotted 22 sx 20/40 sand on RBP. Set 5-1/2" cement retainer @ 10680' and spotted 75 sx H Neat w/additives. Squeezed wolfcamp perms 10707-82' w/50 sx. Drilled retainer and cement. Set RBP @ 11200' and spotted 2 sx 20/40 sand on RBP. Set 5-1/2" cement retainer @ 11020' and squeezed w/150 sx H Neat w/additives. Set 5-1/2" cement retainer @ 11730' and spotted 100 sx H Neat w/additives. Squeezed Lower Canyon perms 11761-81' w/50 sx. Drilled retainer and cement. Perforated Morrow (6 spf) 13224-32', 13239-48' w/114 - .42 holes. Acidized w/1500 gal 7-1/2% Morrow acid w/1000 SCF N2/bbl and 60 balls. Pumped 1000 gal 7-1/2% Morrow acid. Frac'd w/54180 gal 60Q Binary foam w/36500# 20/40 Bauxite Prop.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stormi Davis TITLE Regulatory Compliance Technician DATE 1/30/03

Type or print name Stormi Davis Telephone No. 505-748-1471

(This space for State use)

APPROVED BY _____ TITLE ORIGINAL SIGNED BY PAUL F. KAUTZ PETROLEUM ENGINEER DATE FEB 10 2003

Conditions of approval, if any:

5.1.3