

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy _____ 1648	T. Canyon _____ 11270	T. Ojo Alamo _____	T. Penn "B" _____
T. Salt _____	T. Strawn _____ 11830	T. Kirtland-Fruitland _____	T. Penn "C" _____
B. Salt _____	T. Atoka _____ 12050	T. Picured Cliffs _____	T. Penn "D" _____
T. Yates _____ 2950	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancoos _____	T. McCracken _____
T. San Andres _____ 4610	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____ 6118	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbery _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____ 7410	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo _____ 8638	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 10200	T. _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____ 11,118	T. _____	T. Penn "A" _____	T. _____

### OIL OR GAS SANDS OR ZONES

No. 1, from 12,454' to 12,468' No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

### IMPORTANT WATER SANDS

Includes data on rate of water inflow and elevation to which water rose in hole.  
 No. 1, from \_\_\_\_\_ to \_\_\_\_\_ feet  
 No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet  
 No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet

### LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0	400	400	Sand, Gravel				
400	2500	2100	Salt & Red Beds				
2500	4610	2110	Sand, anhydrite & lime				
4610	7410	2800	Lime, Sand				
7410	10200	2790	Shale, Dolomite				
10200	12750	2550	Lime, Sand, Shale				