

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

6. LEASE DESIGNATION AND SERIAL NO.

LC 015710-A

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL GAS WELL OTHER

7. UNIT AGREEMENT NAME

Lusk Deep Unit

2. NAME OF OPERATOR

El Paso Products Company

8. FARM OR LEASE NAME

Lusk Deep Unit

3. ADDRESS OF OPERATOR

c/o Hobbs Pipe & Supply Co., Box 2010, Hobbs, N. M.

9. WELL NO.

7

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

10. FIELD AND POOL, OR WILDCAT

Lusk

1650' FSL & 990' FWL

11. TOWNSHIP, RANGE, MERIDIAN, OR BLM. AND SURVEY OR AREA

20-19S-32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

UK

12. COUNTY OR PARISH 13. STATE

Lea

N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

PROPOSED PLUGGING PROCEDURES:

1. Spot a 25 sx cement plug to cover existing perforations.
2. Spot a 25 sx cement plug at stub of 4-1/2" casing.
3. Spot a 35 sx cement plug at base of 8-5/8" casing. - (3774')
4. Spot a 25 sx cement plug at 2400' - 2500'.
5. Spot a 25 sx cement plug at 700' - 800'.
6. Spot a 10 sx cement plug at top.
7. Hole will be loaded with mud-laden fluids and a 4" regular marker erected.

18. I hereby certify that the foregoing is true and correct

SIGNED

D. Lusk

TITLE

Agent

DATE

9/16/71

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

DATE

SEP 17 1971

*See Instructions on Reverse Side

J L GORDON
DISTRICT ENGINEER

Faint, illegible text, possibly bleed-through from the reverse side of the page.

RECEIVED

SEP 21 1971

OIL CONSERVATION COMM.
HOUSTON, TEXAS