

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions reverse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC 069276

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS 63240

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Pennzoil Company

3. ADDRESS OF OPERATOR
P.O. Drawer 1828, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FEL & 660' FNL of Sec. 29, T18S R33E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hudson Federal "29"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Corbin, South

11. SEC., T., R., M., OR B.L. AND SURVEY OR AREA

Sec. 29, T18S R33E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3799' GL

12. COUNTY OR PARISH

Lea

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Recompletion

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Completed Operations:

1. Set CIBP @ 12,160' - Dumped 35' (5 sxs) CL "H" cement on top of plug.
2. Set CIBP @ 10,500' - Tested casing to 2000 psi - Dumped 35' (5 sxs) CL "H" cement on top of plug.
3. Perforated Bone Spring from 9081'-9115', 2 SPF, CNL measurements (total of 69 holes)
4. Ran Baker Model "R" Packer and 2 7/8", 6.5#, N-80 tubing - set packer at 9000' w/15,000# compression.
5. Acidized w/5000 gals. 15% gelled HCL acid.
6. Zone tested water w/trace of oil and gas.
7. Shut-in pending further evaluation.

ACCEPTED FOR RECORD

[Signature]
MAR 30 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Randy Hodgins

TITLE Petroleum Engineer

DATE 3/24/87

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side

[Handwritten notes]