

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.B.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-3674	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Amoco Production Company		8. Farm or Lease Name State HQ
3. Address of Operator P. O. Box 68 Hobbs, NM 88240		9. Well No. 42
4. Location of Well UNIT LETTER I 1780 FEET FROM THE South LINE AND 480 FEET FROM THE East LINE, SECTION 26 TOWNSHIP 18-S RANGE 34-E N.M.P.M.		10. Field and Pool, or Wildcat Airstrip Wolfcamp
15. Elevation (Show whether DF, RT, GR, etc.) 3975' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 10800' and ran 23#, 26# and 29# N-80 7" casing set at 10800'. Cemented with 1100 SX Trinity Lite with .75% CFR-2 and 1/4# Flocele/SX and with 600 SX Class H cement with .75% CFR-2 and 5# salt/SX. Plugged down at 9:45 a.m. 8-2-80. Ran temp survey. Top of cement found at approx. 3925'. Will test casing when service unit is moved in.

0+4-NMOCD, H 1-Hou 1-Susp 1-LBG 1-Wayne Stafford, Hou  
1-Bass 1-Mesa 1-Superior 1-Pacific Lighting 1-Southland Royalty

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Davis TITLE Administrative Analyst DATE 8-21-80

Orig. Signed By  
Jerry Sexton

APPROVED BY Jim L. Supa TITLE Supervisor DATE AUG 28 1980

CONDITIONS OF APPROVAL, IF ANY: