

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 063530

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sherri-Dawn Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Lusk Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15, T19S, R32E

12. COUNTY OR PARISH 13. STATE

Lea

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)

1.

OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

PETROLEUM DEVELOPMENT CORPORATION

3. ADDRESS OF OPERATOR

9720 B Candelaria, NE, Albuquerque, NM 87112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

660' from the North Line, 660' from the West line, Sec. 15, T19S, R32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3632 G.L.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Intermediate Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-19-80 Intermediate Casing -
4200' on trip, ran 41 jts. of 8-5/8"-32# casing, 1764.45', plus
60 jts. 8-5/8"-24# casing, 2437.55', set @ 4200'.

Stage #1

Cemented with 600 sx. BJ Lite with 7.5# salt & 1/4# cello flake/sk., 150 sx. Class "C" 2.6# salt/sk.

Stage #2

Cemented with DV tool @ 1075' with 400 sx. BJ Lite, 2% CaCl plus 1/4# cello flake/sk. followed with 100 sx. Class "C", 2% CaCl. Had full returns while cementing both stages. Circulated out 25 sx.. Plug down 8 am 3-19-80. Test 8-5/8" casing and BOP to 2000#.

RECEIVED

MAR 24 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Charles W. Sanders

TITLE Vice President

DATE 3-20-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY:

ACCEPTED FOR RECORD
MAR 26 1980
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

