

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG 1543

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation	8. Farm or Lease Name State DW
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702	9. Well No. 8
4. Location of Well UNIT LETTER 0 710 FEET FROM THE South LINE AND 1830 FEET FROM THE East LINE, SECTION 12 TOWNSHIP 18S RANGE 33E NMPM.	10. Field and Pool, or Wellcat (Bone Mescalero Escarpe Spring)
15. Elevation (Show whether DF, RT, GR, etc.) 4096' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 9080' Dolomite & Anhydrite. Waiting on completion unit. Drilled a 7-7/8" hole from 3150' to a T.D. of 9080' in Dolomite & Anhydrite. Ran and set 160 Jts(6692.98') 5-1/2" OD 15.5# and 56 Jts(2383.70') 5-1/2" OD 17# casing @ 9072' and cemented w/2550 sacks of Class H-Pozmix 50-50 w/3# salt & 0.3 of 1% FLAC/sack cement. PD @ 0715 CDT on 10-12-84. WOC 4 hrs. Ran temp. survey. TOC @ 3100'. ND BOP's, set slips, CO casing & NU WH.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dan C. Zimmerman TITLE Region Petroleum Engineer DATE 10-16-84
APPROVED BY CH 2 TITLE DATE 10-16-84
CONDITIONS OF APPROVAL, IF ANY: