

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUBMIT IN TRIPlicate
(Give instructions on
reverse side)

5. LEASE DESIGNATION AND SERIAL NO.

NM-0245247

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Edith Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Undes. E.K. Bone Springs

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA

Sec 25, T18S, R33E

12. COUNTY OR PARISH 13. STATE

Lea

N.M.

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Manzano Oil Corporation 505/623-1996

3. ADDRESS OF OPERATOR
P.O. Box 571, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
2130' FNL & 660' FWL of Section 25

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, ST, OR, etc.)
3855.4 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

Spud well & run casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/18/85 Spudded well @ 7:30 a.m. 8/18/85 with WEK Drilling, Inc. Rig #2 rotary rig. Drilled 17-1/2" hole to 353'. Ran 9 jts 13-3/8" 54.5# (365.84') casing. Set and cemented @ 353' with 350 sacks Class C cmt with 2% CaCl. Circulated 130 sacks to surface. Plug down @ 7:10 p.m. 8/18/85.

8/25/85 Drilled to 3700'. Ran 91 jts (3708') 24 & 32# 8-5/8" casing, set & cemented @ 3700' with 1300 sks Halliburton Lite cmt w/15# salt & 1/4# floreal per sk followed by 300 sks Class C w/2% CaCl. Circulated 125 sks to surface. Plug down @ 11:45 p.m. 8/24/85. Pressure casing and plug to 1500#.

18. I hereby certify that the foregoing is true and correct

SIGNED Jackie Midkiff TITLE Jackie Midkiff/Prod. Clrk. DATE 8/27/85

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

SEP 3 1985

*See Instructions on Reverse Side

RECEIVED

SEP -9 1985

O.C.D.
HOBBS OFFICE