

WRS COMPLETION REPORT

COMPLETIONS SEC 27 TWP 17S RGE 33E
PI# 30-T-0007 03/21/88 30-025-30072-0000 PAGE 1

NMEX LEA * 1980FNL 1980FWL SEC SE NW
STATE COUNTY FOOTAGE SPOT
PHILLIPS PET D DO
OPERATOR WELL CLASS INIT FIN
29 PHILMEX
WELL NO. LEASE NAME
4167KB 4158GR MALJAMAR
OPER ELEV FIELD POOL AREA
API 30-025-30072-0000

LEASE TYPE NO PERMIT OR WELL I.D. NO
12/07/1987 02/07/1988 ROTARY OIL
SPUD DATE COMP. DATE TYPE TOC. STATUS
4900 GRBG-SAD ARTESIA FSHG TOOL 2 RIG SUB 8
PROJ. DEPTH PROJ. FORM CONTRACTOR
DTD 4800 PB 4650 FM/TD SN ANDRS
DRILLERS T.D. LOG T.D. PLUG BACK TO OLD T.D. FORM T.D.

LOCATION DESCRIPTION

7 MI SE MALJAMAR, NM

CASING/LINER DATA

CSG 8 5/8 @ 1480 W/ 1000 SACKS
CSG 5 1/2 @ 4800 W/ 1700 SACKS

TUBING DATA

TBG 2 3/8 AT 4616

INITIAL POTENTIAL

IPP 22BOPD 37 MCFD 130BW 24HRS
GRAYBURG PERF W/ 2/FT 4177- 4474 GROSS
SN ANDRS PERF W/ 2/FT 4514- 4631 GROSS
GTY 36.2 GOR 1682
FIELD /RESERVOIR
/GRAYBURG-SAN ANDRES

COMMINGLED

TYPE	FORMATION	LTH	TOP	DEPTH/SUB	BSE	DEPTH/SUB
LOG	RUSTLER		1410	2757		
LOG	SALT		1570	2597	1595	2572
LOG	QUEEN		3735	432		
LOG	GRAYBURG		4110	57		
LOG	SN ANDRS		4476	-309		

CONTINUED IC# 300257030787

COMPLETIONS SEC 27 TWP 17S RGE 33E
 PI# 30-T-0007 03/21/88 30-025-30072-0000 PAGE 2

PHILLIPS PET PHILMEX D DO
 29

 CORES

CORE 1 4280- 4303 REC 23.00FT GRAYBURG CONV D
 NO DESCRIPTION AVAILABLE
 CORE 2 4306- 4363 REC 57.00FT GRAYBURG CONV D
 NO DESCRIPTION AVAILABLE
 CORE 3 4363- 4423 REC 60.00FT GRAYBURG CONV D
 NO DESCRIPTION AVAILABLE
 CORE 4 4423- 4483 REC 24.00FT GRBG-SAD CONV D
 NO DESCRIPTION AVAILABLE
 CORE 5 4485- 4517 REC 32.00FT SN ANDRS CONV D
 NO DESCRIPTION AVAILABLE

 PRODUCTION TEST DATA

PTP 11BOPD 145BW 24HRS
 GRAYBURG PERF W/ 2/FT 4177- 4474 GROSS
 SN ANDRS PERF W/ 2/FT 4514- 4708 GROSS
 PERF 4177- 4179 4182- 4186 4236- 4240 4265- 4267
 PERF 4273- 4277 4336- 4338 4352- 4356 4370- 4372
 PERF 4397- 4400 4410- 4413 4429- 4431 4457- 4460
 PERF 4470- 4474 4514- 4518 4523- 4528 4536- 4546
 PERF 4621- 4631 4690- 4708
 ACID 4177- 4708 8600GALS
 15% NEFE HCL
 SWFR 4177- 4708 64000GALS 120000LBS SAND

ADDTVGELA

X-LINK 2% KCL WTR
 20/40 MESH
 PERF W/172 SHOTS TOTAL
 COMMINGLED

PTP 15BOPD 139BW 24HRS
 GRAYBURG PERF 4177- 4479 GROSS
 SN ANDRS PERF 4514- 4708 GROSS
 COMMINGLED

PTP 22BOPD 130BW 24HRS
 GRAYBURG PERF 4177- 4474 GROSS

CONTINUED

COMPLETIONS SEC 27 TWP 17S RGE 33E
PI# 30-T-0007 03/21/88 30-025-30072-0000 PAGE 3

PHILLIPS PET D DO
29 PHILMEX

PRODUCTION TEST DATA

SN ANDRS PERF 4514- 4631 GROSS
PERF 4690- 4708
BRPG 4690- 4708 DEPTH 4650
COMMINGLED

LOGS AND SURVEYS /INTERVAL,TYPE/

LOGS 2500- 4800 DLL 2500- 4800 MSFL 2500- 4800 GR
LOGS 2500- 4800 CAL 2500- 4800 CNL 2500- 4800 LDT
LOGS 0- 2500 CNL 0- 2500 GR 0- 2500 CAL
LOGS 3500- 4718 GR 3500- 4718 CCL

DRILLING MEDIA /TYPE,DEPTH/

4306 10.1 PPG

DRILLING PROGRESS DETAILS

PHILLIPS PET
4001 PENBROOK RM 401
ODESSA, TX 79762
915-367-1266
09/29 LOC/1987/
12/17 4280 TD, PREP CORE
12/17 DEV SURVEY @ 269 (0.50 DEG), 582 (0.50 DEG), 854
(0.50 DEG), 1758 (1.25 DEG), 2195 (0.75 DEG),
2696 (0.25 DEG), 3196 (0.25 DEG), 3708 (0.50
DEG)
12/18 DRLG 4306, VIS 31
12/29 4800 TD, PB 4755, WOCT
01/14 4800 TD, PB 4755, PREP TEST
01/26 4800 TD, PB 4755, PREP SWB
02/01 4800 TD, PB 4755, TOP
02/03 4800 TD, PB 4755, TSTG
02/09 4800 TD, PB 4650, WOPT
02/16 4800 TD, PB 4650, WOPT
03/14 TD REACHED 12/23/87 RIG REL 12/23/87
4800 TD, PB 4650
COMP 2/7/88, IPP 22 BO, 37 MCFG, 130 BWPD,
GOR 1682, GTY 36.2
PROD ZONE - GRAYBURG-SAN ANDRES 4177-4631
(COMMINGLED)

CONTINUED

