



WELL CHRONOLOGY REPORT

REPORT DATE : 12/30/97 MD : 0 TVD : 0 DSS : 19 DOL : 18 MW : VISC :

DAILY DETAILS : UNSET PKR & TOOH, REMOVE PKR. RIH W/4 3/4" BIT, 6 - 3 1/2" DC'S & 2 3/8" TBG. TAGGED UP ON CMT @ 4793'. RU POWER SWIVEL & DRLD GOOD CMT TO 4973'. GOT OUT OF CMT. CIRC HOLE CLEAN. PRESSURED TO 550 PSI IN 30 MINS. HAD 545 PSI & SMALL DRIP @ BOP. RELEASE PRESSURE, TOH W/TBG, DC'S & BIT. CLOSE WELL IN.

REPORT DATE : 12/31/97 MD : 0 TVD : 0 DSS : 20 DOL : 19 MW : VISC :

DAILY DETAILS : RAN RETIEVING HEAD & 158 JTS. 2 3/8" TBG. CIRC SAND OFF OF RBP. GOT ON & RELEASED RBP. TOH & LD RBP. TIH W/4 3/4" BIT & TBG. TAGGED TD @ 6570'. CIRC HOLE W/170 BBLS LEASE WTR. PULLED BIT TO 6520' TO SPOT ACID. SD.

REPORT DATE : 1/1/98 MD : 0 TVD : 0 DSS : 21 DOL : 20 MW : VISC :

DAILY DETAILS : RU PETROPLEX, BROKE CIRC, SPOTTED 500 GALS ACETIC ACID 10% W/BIT @ 6520'. RD PETROPLEX. TOH W/TBG. RU PRO-LOG WL TRK, GOT ON DEPTH & PERF 6492' - 6520', 2 SPF, USING 19 GRAM CHARGES VIA A HOLLOW STEEL CARRIER. 58 SHOTS. RD WL TRK. PU & RAN 5 1/2" ARROWSET 11 TREATING PKR, 202 JTS 2 3/8" W/SN & SET @ 6398'. CLOSE WELL IN.

REPORT DATE : 1/2/98 MD : 0 TVD : 0 DSS : 22 DOL : 21 MW : VISC :

DAILY DETAILS : RU PETROPLEX, LOADED CSG W/6BBL, PERSSURED TO 500 PSI. HELD OK. ACIDIZED PERFS 6490' - 6520' W/3500 GALS NEFE HCL CONTAINING 4 GAL EPC NON EMULSIFIED, 4 GAL I3 CORROSION INHIBITOR, 10 1/2 GAL CCL CLAY CONTROL, 18 GAL LCA IRON CONTROL. USED 40 BALL SEALERS. SLIGHT BALL ACTION. FLUSHED W/40 BBLS 2% KCL WATER. AVG RATE 4.9, MAX RATE 5 BPM, AVG PRESS 2800 PSI, ON VAC 2 MIN. RD PETROPLEX, WAIT 30 MIN. RU SWAB. 124 BLTR. BEGINNING FL 3000' FROM SURFACE. SWABBED TO SN IN 3 HRS. SWABBED TOTAL OF 6 HRS. & RECOVERED 27 BBL WTR. LEFT WELL OPEN TO TANK ON 10/64" CHOKE.

REPORT DATE : 1/3/98 MD : 0 TVD : 0 DSS : 23 DOL : 22 MW : VISC :

DAILY DETAILS : SDFWE

REPORT DATE : 1/4/98 MD : 0 TVD : 0 DSS : 24 DOL : 23 MW : VISC :

DAILY DETAILS : SDFWE

REPORT DATE : 1/5/98 MD : 0 TVD : 0 DSS : 25 DOL : 24 MW : VISC :

DAILY DETAILS : WELL OPEN TO TANK 66 HRS. ON 10/64". FL @ 5600'. RD SWAB. UNSET PKR & TOH W/TBG. RAN 1 JT. BULL PLUG MA, 2 3/8" X 4' PERF SUB, 2 3/8" SN & 206 JTS 2 3/8" TBG W/2 3/8" X 5 1/2" TAC, 4 JTS ABOVE SN. BOTTOM OF MA @ 6554'. SN @ 6517'. TAC @ 6389'. ND BOP & NU WELLHEAD. RAN 20 X 125 RHBC 20 X 5 X 3 X 1 PUMP, 8-1 1/2" K-BARS, 129 3/4" RODS, 122 7/8" RODS, 18'-7/8" SUBS & 1 1/4" X 22 POLISH ROD. CLOSE WELL IN.