

ATTACHMENT

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT  
OIL CONSERVATION DIVISION

FORM C-105

SEELY OIL COMPANY  
CENTRAL EK QUEEN UNIT WELL #12  
NW/4 SW/4 SECTION 8, 18S, 34E  
LEA COUNTY, NEW MEXICO

23. Casing Record:

8-5/8" OD, 23# surface casing cemented with 580 sxs 65/35 Class C w/1/4# of Celoflake/sx followed by 250 sxs Class C w/1/4# of Celoflake/sx & 2% CaCl. Plug down 9:00 p.m. 7/17/97.

4-1/2" OD, 11.6# casing cemented w/225 sxs Halliburton Lite w/9# salt/sx followed by 150 sxs Premium Pozmix w/6# salt/sx & 1% CFR-3. Plug down @ 11:05 p.m. 7/23/97. Top of cement @ 3014' RKB.

27. Acid, Shot, Fracture, Cement, Squeeze, Etc.

8/1/97      4378-86'      Acidized w/1000 gals. 15% MCA utilizing ball sealers to ball out.

8/3/97      4378-86'      Fracture treated w/10,000 gals. gelled wtr. w/15,500# 16/30 sand.