Submit 3 Copies

ate of New Mexico

Form C-103

Energy, Mincials and Natural Resources Department Revised 1-1-89 to Appropriate District Office OIL CONSERVATION DIVISION DISTRICT I WELL API NO. P.O. Box 1980, Hobbs NM 88241-1980 2040 Pacheco St. 30-025-36046 **DISTRICT II** Santa Fe. NM 87505 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 STATE [FEE X DISTRICT III 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Hobbs Deep 'A' 1. Type of Well: OIL X 8. Well No. 2. Name of Operator Occidental Permian Limited Partnership 9. Pool name or Wildcat 3. Address of Operator P.O. Box 4294, Houston, TX 77210-4294 Wildcat: Tubb. Drinkard. Abo 4. Well Location 990 660 SHL: Unit Letter South East Feet From The Line and Feet From The Line 330 BHL: South 660 East Section 13 Township Range 37-E **NMPM** Lea County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3671' GL 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: **NOTICE OF INTENTION TO:** PERFORM REMEDIAL WORK PLUG AND ABANDON ALTERING CASING REMEDIAL WORK COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT **CHANGE PLANS TEMPORARILY ABANDON** CASING TEST AND CEMENT JOB L **PULL OR ALTER CASING** OTHER: Run 7" Casing OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 12/4/02 -12/6/02: Run 158 jts. 7", 26#, J-55, LT&C casing with 24 centralizers and set at 6553' (MD). Cement first stage w/675 sx. Premium Plus. Plug down. Open DV tool. Circulate 192 sx. off DV tool. Cement second stage w/700 sx. Interfill 'C' x 100 sx. Premium Plus. Plug down and circulate 303 sx. to surface. ND BOP x set casing slips x cut off 7" casing. NU BOP x test blind rams. pipe rams, wellhead, annular, manifold, HCR valve, and safety valves to 3000 psi x 30 min. Run 6-1/8" bit x drill out DV tool. Test casing to 1500 psi x 30 min. PU directional drilling tools x start in hole x resume directional drilling. 12/12/02: Log open hole x tag TD at 7745' (MD); 7640' (TVD) 12/14/02: Release drilling rig at 12:01 p.m. (12/14/02) I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE Business Analyst (SG) DATE TELEPHONE NO. TYPE OR PRINT NAME Mark Stephens (This space for State Use) ORIGINAL SIGNED BY PAUL F. KAUTZ PETROLEUM ENGINEER DATE. APPROVED BY CONDITIONS OF APPROVAL, IF ANY: