

LOG AND HISTORY

WELL NO. 4 PROPERTY State 3 STANDARD OIL CO. OF TEXAS COMPANY

NOTE: FORMATIONS SHOWING OIL OR GAS SHOULD BE NOTED IN CAPITALS

FROM	TO	FEET	FORMATION DRILLED AND CORED
			<p>6 P.M. to 8 P.M. - 36 bbl.</p> <p>8 P.M. to 6 A.M. - 147 " .6% cut</p> <p>6 A.M. to 7 A.M. - 15-1/2 bbl..6% cut</p>
			<p><u>April 1, 1940:</u></p> <p>Completed a 24-hour official potential test. Well flowed 304 bbl. of oil through open 2" tubing. Tubing pressure at end of test was 12" and casing pressure 460.</p> <p>The well was allowed to continue to produce after the 24-hour test and it produced 57 bbl. of oil from 7 A.M. to 10 A.M.</p> <p>The well was equipped with a 9-5/8" x 7" Braden-head in order to allow the use of sweet gas encountered from 2995' - 3045'.</p> <p>After drilling to T.D. it was noticed that gas was escaping through the insert clamps between the 9-5/8" and 13-3/8" casing. The insert clamps were welded to casing and pressure between 9-5/8" and 13-3/8" casing built up to 425#.</p> <p>CONTRACTOR: Loffland Brothers</p>
			<p>DRILLERS:</p> <p>W. A. Stewart</p> <p>H. M. Taylor</p> <p>R. B. Hanson</p> <p>Fred H. Gray</p> <p>T. A. Beavers</p> <p>C. C. Taylor</p>
			<p>H. J. BARNES</p> <p><i>H. J. Barnes</i></p>
			<p>HMB/EF</p>
			<p>April 15, 1940.</p>

