

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN AN OLD WELL IN A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT TO DRILL OR TO REOPEN AN OLD WELL FOR FURTHER DETAILS.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator Getty Oil Company	8. Form or Lease Name C. S. Caylor
3. Address of Operator P. O. Drawer DD, Levelland, Texas 79336	9. Well No. 1 4
4. Location of Well UNIT LETTER G 2179 FEET FROM THE North LINE AND 2173 FEET FROM THE East LINE, SECTION 6 TOWNSHIP 17-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat Lovington - Abo
11. Elevation (Show whether DF, RT, GR, etc.) GR 3818	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

SQUEEZE HOLE IN CASING:

- POH w/rods & pump. Installed BOP. Released tbq. anchor, POH w/tbg.
- RIH w/5-1/2" R.T.T.S. packer & retrievable B.P. Set B.P. @ 7546'. Set R.T.T.S. pkr. @ 7541' & tested B.P. @ 2000#, O.K. Circulated hole w/2% KCL water.
- Located hole in 5-1/2" csg. between 4945' to 5010'.
- Ran Dresser Atlas Vertilog Casing Inspection log. Holes @ 5000' & 5042' and possible holes @ 5008' & 5028'.
- Re-set R.T.T.S. pkr. @ 4800'. Squeezed holes from 5010' back to 4995' w/50 sx. Class "C" cmt.
- Re-set R.T.T.S. pkr. @ 4680', pressured up to 3500# SIP, WOC.
- POH w/R.T.T.S. pkt. RIH w/4-5/8" bit. Drilled hard cement from 4770' to 5015'.
- Circulated hole, retrieved B.P.
- Ran production materials.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

E. P. Morales
E. P. Morales TITLE area engineer DATE 6-5-80

APPROVED BY _____ TITLE _____ DATE 6-5-80
CONDITIONS OF APPROVAL, IF ANY