

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O. C. C.  
NEW MEXICO OIL CONSERVATION COMMISSION  
APR 28 3 19 PM '66

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-4413
7. Unit Agreement Name
8. Farm or Lease Name State "E"
9. Well No. 1
10. Field and Pool, or Wildcat Undesignated
12. County Los

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <b>Dry</b>
2. Name of Operator <b>Midwest Oil Corporation</b>
3. Address of Operator <b>1500 Wilco Building Midland, Texas</b>
4. Location of Well UNIT LETTER <b>E</b> <b>560</b> FEET FROM THE <b>West</b> LINE AND <b>2010</b> FEET FROM THE <b>North</b> LINE, SECTION <b>10</b> TOWNSHIP <b>17-S</b> RANGE <b>37-E</b> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) <b>3762.7 GL</b>

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-12-66 Spudded.

3-12-66 Ran 8 jts 13 3/8" 35.6 # csg to 317' Cemented w/350 sax reg. plug 2% cc. Cement circulated. WOC 18 hours. Tested csg to 300 Test held.

3-19-66 Ran 137 jts 8 5/8" 24# and 32# to 4480'. Cemented w/300 sax Incor w/4% gel and 100 sax Incor w/2%cc.

4-5-66 Plugged and Abandoned: Spotted cement plugs as follows: 25 sax @ 8800, 25 sax @ 7500, 25 sax @ 6600, 25 sax @ 5050, 25 sax @ 4500, 10 sax at surface. Welded marker on top of 13 3/8" csg. Filled bellared and leveled location. Will advise when pits have been filled and ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED McIntire

TITLE **District Clerk**

DATE **4-20-66**

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

**SUPERVISOR**

**APR 28 1966**

