5, LEDASE

UNITED STATES DEPARTMENT OF THE INTERIOR

CECLOGICAL SURVEY DTICES AND REPORTS ON WELLS or proposals to drill or to decemen ar plug back to a different all other matter of the management of the decement of plug back to a different of the management of the decement of plug back to a different of the management of the decement of the decement of the decement of the management of the decement of the decement of the decement of the management of the decement of the decem	DEPARTMENT OF THE INTERIOR	29-00086
8. FARM OR LEASE NAME Superior Federal 9. WELL NO. 8-X 10. FIELD OR WILDCAT NAME Pearl Seven Rivers 11. SEC., T., R., M., OR BLK. AND SURVEY OF Sec. 25, T-19-S, R-34-E 11. POSED OR COMPLETED OPERATIONS (Clearly state all pertinent details; and give pearlinent dates of date of starting any proposed work. If well is directionally drilled, give subsurfate occations and section and grown pearlinent to this work.)* SX Bottom Plug over Perfs. 3967-4075 Issing. Set 20 sx plug 3100-2950'. Tag plug. sx plug @ 2130' - Base Salt sx plug @ 2130' - Bottom of 8 5/8" Surface Casing. sx plug @ 210' - Bottom of 8 5/8" Surface Casing. sx plug @ 210' - Bottom of 8 5/8" Surface Casing. sx plug @ 210' - Bottom of 8 5/8" Surface Casing. sx plug @ 1750' - Top Salt sx plug @ 1750' - Top Salt sx plug @ 1750' - Top Salt sx plug @ 1750' - Bottom of 8 5/8" Surface Casing. sx plug @ 1750' - Top Salt sy plug @ 1750' - Top Salt	GEOLOGICAL SURVEY	
Superior Federal Superior Federal 9. WELL NO. 8-X 10. FIELDOR WILLDAT NAME Pearl Seven Rivers 11. SEC., T., R., M., OR BLK. AND SURVEY OF SEC. 25, T-19-S, R-34-E 12. COUNTY OR PARISH 13. STATE Lea New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD 3762 KDB ASING ROVAL TO: SUBSEQUENT REPORT OF: 16. SUBSEQUENT REPORT OF: 17. SUBSEQUENT REPORT OF: 18. SEC. 25, T-19-S, R-34-E 19. WELL NO. 8-X 10. FIELDOR WILLDAT NAME Pearl Seven Rivers 11. SEC., T., R., M., OR BLK. AND SURVEY OF SEC. 25, T-19-S, R-34-E 12. COUNTY OR PARISH 13. STATE Lea New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD 3762 KDB 16. SUBSEQUENT REPORT OF: 17. SUBSEQUENT REPORT OF: 18. SUBSEQUENT REPORT OF: 18. SUBSEQUENT REPORT OF: 19. WELL NO. 11. SEC., T., R., M., OR BLK. AND SURVEY OF SEC. 25, T-19-S, R-34-E 12. COUNTY OR PARISH 13. STATE Lea New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD 3762 KDB (NOTE: Report results of multiple completion or zon change on Form 9-330.) 19. WELL NO. 10. AREA APEROVE DEVISION OF BROWN OF SEC. 25, T-19-S, R-34-E 11. SEC., T., R., M., OR BLK. AND SURVEY OF SEC. 25, T-19-S, R-34-E 11. SEC., T., R., M., OR BLK. AND SURVEY OF SEC. 25, T-19-S, R-34-E 11. SEC., T., R., M., OR BLK. AND SURVEY OF SEC. 25, T-19-S, R-34-E 11. SEC., T., R., M., OR BLK. AND SURVEY OF SEC. 25, T-19-S, R-34-E 12. COUNTY OR PARISH 13. STATE Lea New Mexico 14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD 3762 KDB 3762 KD	SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	
POSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and gave paralinent dates stated date of starting any proposed work. If well is directionally drilled, give subsurface locations and use vertical depths for all markers and zones pertinent to this work.) SX Bottom Plug over Perfs. 3967-4075' SX Plug @ 2130' - Base Salt SX Plug @ 2130' - Base Salt SX Plug @ 251' - Bottom of 8 5/8" Surface Casing. SX Splug @ 251' - Bottom of 8 5/8" Surface Casing. SX Splug @ Surface Plug	1. oil gry gas	
POPERATOR NATION SUBSEQUENT REPORT OF: OPSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and gave pertinent to this work.)* SECURITY STATE OF SUBSEQUENT REPORT OF: OPSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and gave pertinent to this work.)* SECURITY STATE OF SUBSEQUENT REPORT OF: OPSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and gave pertinent to this work.)* OPSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and gave pertinent to this work.)* SECURITY STATE (NOTE Report results of multiple completion or zon change on form 9-330.) (NOTE REPORT OF: OPSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and gave pertinent to this work.)* SECURITY STATE OF	2. NAME OF OPERATOR	/
Nati Bank Bldg, Midland, TX 79701 WELL (REPORT LOCATION CLEARLY. See space 17 Unit I 1980' FSL & 660' FEL, Sec. 25, TH: T-19-S, R-34-E PRIATE BOX TO INDICATE NATURE OF NOTICE. THER DATA ROVAL TO: SUBSEQUENT REPORT OF: OFF WELL OF SUBSEQUENT REPORT OF: ON TE Report results of multiple completion of zon change on Form 9-330.) IN OTE Report results of multiple completion of zon change on Form 9-330.) ON TE Report results of multiple completion of zon change on Form 9-330.) ON TE Report results of multiple completion of zon change on Form 9-330.) ON TE Report results of multiple completion of zon change on Form 9-330.) ON TE Report results of multiple completion of zon change on Form 9-330.) IN OTE Report results of multiple completion of zon change on Form 9-330.) TO SUBSEQUENT REPORT OF: ON TE Report results of multiple completion of zon change on Form 9-330.) TO SUBSEQUENT REPORT OF: ON TE REPORT FEBLUAR AND WD 3762 KDB. AND WD 3762 KDB. IN OTE Report results of multiple completion of zon change on Form 9-330.) IN OTE Report results of multiple completion of zon change on Form 9-330.) TO SUBSEQUENT REPORT OF: ON TE REPORT FEBLUAR AND WD 3762 KDB. AND WD 3762 KDB. IN OTE REPORT FEBLUAR AND WD 3762 KDB. AND WD 3762 KDB. ON TE Lea AND NO. IS. ELEVATIONS (SHOW DF, KDB, AND WD 3762 KDB. IN OTE REPORT FEBLUAR AND WD 3762 KDB. IN OTE REPORT FEBLU	St. Clair Energy Corporation 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME
WELL (REPORT LOCATION CLEARLY. See space 17 Unit I 1980' FSL & 660' FFL, Sec. 25, H: T-19-S, R-34-E PRIATE BOX TO INDICATE NATURE OF NOTICE. THER DATA ROVAL TO: SUBSEQUENT REPORT OF: OFF SSING FE SSING SSING FE SSING FE SSING SSING FE SSING SSING FE SSING SS	501 First Nat'l Bank Bldg, Midland, TX 79701	
INTERVAL: T-19-S, R-34-E PRIATE BOX TO INDICATE NATURE OF NOTICE. THER DATA ROVAL TO: SUBSEQUENT REPORT OF: OFF CHARGE GOX ASING CHARGE GOX POSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give paginent dates and accorded to date of starting any proposed work. If well is directionally drilled, give subsurflate locations and rule vertical depths for all markers and zones pertinent to this work.)* SX Bottom Plug over Perfs. 3967-4075' SX Sping. Set 20 sx plug 3100-2950'. Tag plug. Sx plug @ 2130' - Base Salt Sx plug @ 21750' - Top Salt Sx plug @ 261' - Bottom of 8 5/8" Surface Casing. Sx plug @ 261' - Bottom of 8 5/8" Surface Casing. Sx plug @ Surface Position granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. INVE: Manu. and Type Set @ Ft. APPROVILATING space for Federal or State of Federal or State	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit I 1980' FSL & 660'	Sec. 25, T-19-S, R-34-E
PRIATE BOX TO INDICATE NATURE OF NOTICE, THER DATA ROVAL TO: SUBSEQUENT REPORT OF: OFF OSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give perfinent dates ated date of starting any proposed work. If well is directionally drilled, give subsufface locations and rule vertical depths for all markers and zones pertinent to this work.)* SX Bottom Plug over Perfs. 3967-4075' ISSING. Set 20 sx plug 3100-2950'. Tag plug. Sx plug @ 2130' - Base Salt Sx plug @ 1750' - Top Salt Sx plug @ 261' - Bottom of 8 5/8" Surface Casing. Sx plug @ Surface plarker Dission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. Inve: Manu. and Type Set @ Ft. APPROVE Athis space for Federal or State off cause) DATE 4-26-83	AT SURFACE: FEL, Sec. 25, AT TOP PROD. INTERVAL: T. 10.5. D. 24.5	
THER DATA ROVAL TO: SUBSEQUENT REPORT OF: OFF ASING OFF OFF OFF OFF OFF OFF OFF O	AT TOTAL DEFINE.	
POSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates ated date of starting any proposed work. If well is directionally drilled, give subsurface focations and rue vertical depths for all markers and zones pertinent to this work.)* SX Bottom Plug over Perfs. 3967-4075' If 5½" Csg. @ 3050' Approx. Cement Top - 3100' Issing. Set 20 sx plug 3100-2950'. Tag plug. SX plug @ 2130' - Base Salt SX plug @ 1750' - Top Salt SX plug @ 261' - Bottom of 8 5/8" Surface Casing. SX plug @ Surface Plarker Itssion granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. Inverting and Type	REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3762 KDB
POSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates ated date of starting any proposed work. If well is directionally drilled, give subsurface locations and rue vertical depths for all markers and zones pertinent to this work.)* sx Bottom Plug over Perfs. 3967-4075' sing. Set 20 sx plug 3100-2950'. Tag plug. sx plug @ 2130' - Base Salt sx plug @ 2130' - Base Salt sx plug @ 1750' - Top Salt sx plug @ 261' - Bottom of 8 5/8" Surface Casing. sx plug @ Surface plarker rission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. APPROVE Dathis space for Federal or State off course)	TEST WATER SHUT-OFF	
POSED OR COMPLETED OPERATIONS (Clearly state all pertinent details; and give pertinent dates ated date of starting any proposed work. If well is directionally drilled, give subsurface locations and rive vertical depths for all markers and zones pertinent to this work.)* sx Bottom Plug over Perfs. 3967-4075' off 5½" Csg. @ 3050' Approx. Cement Top - 3100' ssing. Set 20 sx plug 3100-2950'. Tag plug. sx plug @ 2130' - Base Salt sx plug @ 1750' - Top Salt sx plug @ 261' - Bottom of 8 5/8" Surface Casing. sx plug @ Surface plarker dission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. Application of the property of the performance of the perform	PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES	change on Form 9–330.)
sx Bottom Plug over Perfs. 3967-4075' off 5½" Csg. @ 3050' Approx. Cement Top - 3100' using. Set 20 sx plug 3100-2950'. Tag plug. sx plug @ 2130' - Base Salt sx plug @ 1750' - Top Salt sx plug @ 261' - Bottom of 8 5/8" Surface Casing. sx plug @ Surface plarker uission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. Ilive: Manu. and Type	ABANDON* □	1915년 - 최기 년년(1)
sx Bottom Plug over Perfs. 3967-4075' off 5½" Csg. @ 3050' Approx. Cement Top - 3100' using. Set 20 sx plug 3100-2950'. Tag plug. sx plug @ 2130' - Base Salt sx plug @ 1750' - Top Salt sx plug @ 261' - Bottom of 8 5/8" Surface Casing. sx plug @ Surface plarker uission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. Ilive: Manu. and Type	(other)	
APPROVED (This space for Federal or State off Course) Ising. Set 20 sx plug 3100-2950'. Tag plug. Ising. Set 20 sx plug 3100-2950'. Tag plug. Is sx plug @ 2130' - Base Salt Is sx plug @ 1750' - Top Salt Is sx plug @ 261' - Bottom of 8 5/8" Surface Casing. Is sx plug @ Surface In state of the stat	 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dir measured and true vertical depths for all markers and zones pertinent 	all pertinent details, and give pertinent dates rectionally drilled, give subsurface locations and to this work.)*
sx plug @ 2130' - Base Salt sx plug @ 1750' - Top Salt sx plug @ 261' - Bottom of 8 5/8" Surface Casing. sx plug @ Surface plarker rission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. A PPROVENTING space for Federal or State off Course)	1) Set 25 sx Bottom Plug over Perfs. 3967-407 2) Shoot off 5½" Csg. @ 3050' Approx. Cement	Top - 3100'
sx plug @ 261' - Bottom of 8 5/8" Surface Casing. sx plug @ Surface plarker dission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. Set @Ft. TITLEAgent	3) Set 25 sx plug @ 2130' - Base Salt	lag plug.
sx plug @ Surface p larker dission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. Alve: Manu. and Type	4) Set 25 sx plug @ 1750' - Top Salt 5) Set 25 sx plug @ 261' - Bottom of 8 5/8" s	
darker dission granted by Armando Lopez with Dept. of Interior B.L.M. agement Section, Roswell, New Mexico on 4-26-83. Application of Interior B.L.M. Set @Ft. TITLEAgent	b) Set 10 sx plug & Surface	burrace casing.
Ilve: Manu. and Type Set @ Ft. TITLE Agent DATE 4-26-83	7) Weld Cap 8) Place Marker	
Ilve: Manu. and Type Set @ Ft. TITLE Agent DATE 4-26-83	Verbal permission granted by Armando Lonez wit	th Dont of Interior D. I. M.
TITLE Agent DATE 4-26-83	Mineral Management Section, Roswell, New Mexic	to on 4-26-83.
TITLE Agent DATE 4-26-83	Subsurface Safety Valve: Manu. and Type	Set @ Ft.
APPROVE Dithis space for Federal or State office use)	18. I hereby certify that the foregoing is true and correct	
APPROVE Dithis space for Federal or State office use)		DATE 4-26-83
DATE OF THE DATE O	APPROVE AThis space for Federal or State office APPROVED Spile Sgd.) PETER W. CHESTER CONDITIONS OF APPROVAL, IF ANY:	P 115 A)