

[illegible][illegible]

Custome Type	Amount	Plant No.	Batch No. Clerk
			Size
MUD DATA			
Mud Type	Wt		
Viscosity	Water to 1		C.C.
Resist. of Mud	F. of Filtrate		°F
Chloride Content			PPM

FOURTH & FIVE YEARS

Type Test		N. E. E. OFF-HOLD
Formation Tested		5500
Elevation		1730
Net productive Interval		00
Estimated Porosity		0
All Depths Measured From		REL. BUS-170
Total Depth		11460
Main Hole Casing Size		7 7/8"
Tub. Hole Liner Size		7"
BCP Casing Length		100' I.D. 3.5"
BCP Pipe Length		107' I.D. 3.5"
Padelr Depth(s)		11300 & 11370

MULTI-FLOW EVALUATOR
FLUID SAMPLE DATA

Sampler Pressure	11.50	P.S.I.G. at Surface
Recovery: Cu. Ft. Gas	11	
cc. Oil	11.5	
cc. Water	-	
cc. Mud	-	
Total Liquid cc	11.5	
Gravity	44.1	°API @ 60 °F.
Gas Oil Ratio	11.5	cu. ft./bbl.

FOR SILENCE

CHLORIDE CONTENT

Recovery Water @ °F. ppm

Recovery Mud @ °F.

Recovery Mud Filtrate @ °F. ppm

Mud Fil Sample 55 @ 46 °F.

Mud Fil Sample Filtrate 1.0 @ 50 °F. 1500 ppm

RECOVERY DESCRIPTION	FEET	D. AREA	FE. CHL	FE. WATER	FE. OTHERS	API GRAVITY	RESISTIVITY	CHL. PPM
1. 10' - 12' - 14' - 16' - 18' - 20' - 22' - 24' - 26' - 28' - 30' - 32' - 34' - 36' - 38' - 40' - 42' - 44' - 46' - 48' - 50' - 52' - 54' - 56' - 58' - 60' - 62' - 64' - 66' - 68' - 70' - 72' - 74' - 76' - 78' - 80' - 82' - 84' - 86' - 88' - 90' - 92' - 94' - 96' - 98' - 100'						@ °F.	@ °F.	
2. 10' - 12' - 14' - 16' - 18' - 20' - 22' - 24' - 26' - 28' - 30' - 32' - 34' - 36' - 38' - 40' - 42' - 44' - 46' - 48' - 50' - 52' - 54' - 56' - 58' - 60' - 62' - 64' - 66' - 68' - 70' - 72' - 74' - 76' - 78' - 80' - 82' - 84' - 86' - 88' - 90' - 92' - 94' - 96' - 98' - 100'						@ 60 °F.	@ °F.	
3. 10' - 12' - 14' - 16' - 18' - 20' - 22' - 24' - 26' - 28' - 30' - 32' - 34' - 36' - 38' - 40' - 42' - 44' - 46' - 48' - 50' - 52' - 54' - 56' - 58' - 60' - 62' - 64' - 66' - 68' - 70' - 72' - 74' - 76' - 78' - 80' - 82' - 84' - 86' - 88' - 90' - 92' - 94' - 96' - 98' - 100'						@ °F.	@ °F.	
4. 10' - 12' - 14' - 16' - 18' - 20' - 22' - 24' - 26' - 28' - 30' - 32' - 34' - 36' - 38' - 40' - 42' - 44' - 46' - 48' - 50' - 52' - 54' - 56' - 58' - 60' - 62' - 64' - 66' - 68' - 70' - 72' - 74' - 76' - 78' - 80' - 82' - 84' - 86' - 88' - 90' - 92' - 94' - 96' - 98' - 100'						@ °F.	@ °F.	
5. 10' - 12' - 14' - 16' - 18' - 20' - 22' - 24' - 26' - 28' - 30' - 32' - 34' - 36' - 38' - 40' - 42' - 44' - 46' - 48' - 50' - 52' - 54' - 56' - 58' - 60' - 62' - 64' - 66' - 68' - 70' - 72' - 74' - 76' - 78' - 80' - 82' - 84' - 86' - 88' - 90' - 92' - 94' - 96' - 98' - 100'						@ °F.	@ °F.	
6. 10' - 12' - 14' - 16' - 18' - 20' - 22' - 24' - 26' - 28' - 30' - 32' - 34' - 36' - 38' - 40' - 42' - 44' - 46' - 48' - 50' - 52' - 54' - 56' - 58' - 60' - 62' - 64' - 66' - 68' - 70' - 72' - 74' - 76' - 78' - 80' - 82' - 84' - 86' - 88' - 90' - 92' - 94' - 96' - 98' - 100'						@ °F.	@ °F.	
7. 10' - 12' - 14' - 16' - 18' - 20' - 22' - 24' - 26' - 28' - 30' - 32' - 34' - 36' - 38' - 40' - 42' - 44' - 46' - 48' - 50' - 52' - 54' - 56' - 58' - 60' - 62' - 64' - 66' - 68' - 70' - 72' - 74' - 76' - 78' - 80' - 82' - 84' - 86' - 88' - 90' - 92' - 94' - 96' - 98' - 100'						@ °F.	1.70 60 °F.	500
8. 10' - 12' - 14' - 16' - 18' - 20' - 22' - 24' - 26' - 28' - 30' - 32' - 34' - 36' - 38' - 40' - 42' - 44' - 46' - 48' - 50' - 52' - 54' - 56' - 58' - 60' - 62' - 64' - 66' - 68' - 70' - 72' - 74' - 76' - 78' - 80' - 82' - 84' - 86' - 88' - 90' - 92' - 94' - 96' - 98' - 100'						@ °F.	@ °F.	

Remarks