

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.

L656

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cotton Petroleum Corporation	8. Farm or Lease Name State L656
3. Address of Operator 816 Bldg. of Southwest, Midland, Texas	9. Well No. 1
4. Location of Well UNIT LETTER <u>N</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>2220.7</u> FEET FROM THE <u>West</u> LINE, SECTION <u>18</u> TOWNSHIP <u>17S</u> RANGE <u>36E</u> NMPM.	10. Field and Pool, or Wildcat Vacuum (Abo Reef)
15. Elevation (Show whether DF, RT, GR, etc.) 3890' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2/7/77 Captioned well was permanently plugged by Halliburton Company this date. 380' 13 3/8", 48# H-40 and 3393', 8 5/8", 32# & 24# K-55, ST&C casing with cement circulated to surface on both strings was left in the hole. The hole was loaded with 9.3 # mud and the following cement plugs were spotted:

35 sx. Class "C" Neat Cement 8760 - 8860'
35 sx. Class "C" Neat Cement 6080 - 6180'
35 sx. Class "C" Neat Cement 3343 - 3443'
35 sx. Class "C" Neat Cement 1700 - 1800'
10 sx. Class "C" Neat Cement Plug at surface

The drilling pad has been cleared of junk and the pits will be leveled in 60-90 days when they have sufficiently dried.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Division Prod. Manager</u>	DATE <u>2/7/77</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>MAY 5 1978</u>
CONDITIONS OF APPROVAL, IF ANY:		