

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State Fee
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry and abandoned	7. Unit Agreement Name
2. Name of Operator Manzano Oil Corporation 505/633-1996	8. Farm or Lease Name Shaw Fee
3. Address of Operator P.O. Box 571, Roswell, NM 88202	9. Well No. 1
4. Location of Well UNIT LETTER H 2130' FEET FROM THE North LINE AND 660 FEET FROM East THE East LINE, SECTION 15 TOWNSHIP 17S RANGE 37E NMPM.	10. Field and Pool, or Wildcat Humble City Strawn
15. Elevation (Show whether DF, RT, GR, etc.) 3746.5 GL	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK
TEMPORARILY ABANDON
PULL OR ALTER CASING
OTHER _____

PLUG AND ABANDON
CHANGE PLANS

SUBSEQUENT REPORT OF:

REMEDIAL WORK
COMMENCE DRILLING OPNS.
CASING TEST AND CEMENT JOB
OTHER _____

ALTERING CASING
PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1/30/85 Drilled 17½" hole to 350', ran & cmtd 13-3/8" casing - see previous report.
 2/9/85 Drilled 12¼" hole to 4500', ran & cmtd 8-5/8" casing - see previous report.
 2/28/85 Ran DST 11,325'-11,500', Open 30" with very weak blow, closed 60", open 60" w/no blow, closed 120", Recovered 100' drilling mud, sampler 2200 cc drilling mud, no show, temperature 165°.
 3/4/85 Ran DST 11,600'- 11,750', Open 30" w/weak blow through flow, closed 60", Open 60" no blow, closed 120", REcovered 540' drlg mud, sampler 2300 cc drlg mud, no shows, temperature 130°.
 3/5/85 Drilled to total depth 11,750'. Ran logs and plugged well as follows:
 Set 8 cement plugs as follows with 40 sacks Class C cmt each, approx 128' each.
 #1 11,600' #2 10,890' #3 9,740' #4 8,525' #5 6,890'
 #6 5,225' #7 4,500' #8 2,170' 40 sacks at surface.
 Set dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jackie Midkiff TITLE Jackie Midkiff/Prod Clrk DATE 4/1/85
 APPROVED BY [Signature] TITLE OIL & GAS INSPECTOR DATE APR 14 1987

CONDITIONS OF APPROVAL, IF ANY:

YM

RECEIVED

APR - 2 1985

HERB S. GIBSON