

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
V-285	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Great Western Drilling Company		8. Farm or Lease Name Bell State
3. Address of Operator P.O. Box 1659, Midland, TX 79702		9. Well No. 1
4. Location of Well UNIT LETTER <u>P</u> <u>837</u> FEET FROM THE <u>South</u> LINE AND <u>570</u> FEET FROM THE <u>East</u> LINE, SECTION <u>17</u> TOWNSHIP <u>19-S</u> RANGE <u>35-E</u> NMPM.		10. Field and Pool, or Wildcat Scharb (BS)
15. Elevation (Show whether DF, RT, GR, etc.) 3,836.4' KB		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPERATIONS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <u>Spud & Cementing of Surface Csg.</u> <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2/14/85: Spudded 17½" hole @ 10:00 a.m., 2-14-85. T.D. 17½" hole @ 419' @ 1:15 p.m., 2-14-85. Ran 10 jts 13-3/8" OD, 48#, H-40, ST&C, csg (391.22') and set @ 411.88' KBM. Cemented w/450 sxs class "C" plus 1/4# flocele & 2% calcium chloride per sack. Circulated excess of 75 sxs. Plug down @ 7:15 p.m., 2-14-85. NMOCC notified but did not witness. WOC 13½ Hrs. Tested csg & BOP to 550 psi for 30 min., held. Drilled cement & plug, now drilling ahead @ 419'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED M. B. Meyer TITLE Ass't. to Gen. Supt. DATE 2-20-85

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT I SUPERVISOR TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 22 1985

RECEIVED

FEB 21 1985

100-2371
HOUSE OFFICE