

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons.
P.O. Box 1980
Hobbs, NM 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well Gas Well Other

2. Name of Operator

Manzano Oil Corporation

3. Address and Telephone No.

P.O. Box 2107, Roswell, NM 88202-2107 (505) 623-1996

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

383' FSL & 652' FWL
Sec 14, T19S, R33E

5. Lease Designation and Serial No.
NM-56749

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Federal USA "L" #9-Y

9. API Well No.
30-025-34347

10. Field and Pool, or Exploratory Area
Tonto Seven Rivers

11. County or Parish, State
Lea

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

Notice of Intent
 Subsequent Report
 Final Abandonment Notice

TYPE OF ACTION

Abandonment
 Recompletion
 Plugging Back
 Casing Repair
 Altering Casing
 Other Beginning Operations

Change of Plans
 New Construction
 Non-Routine Fracturing
 Water Shut-Off
 Conversion to Injection
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/21/98 Day #1. Spud @ 9:00 p.m. 3/20/98.
3/23/98 Ran 44 jts of 24 & 20# - J55 - 8-5/8" - 8R w/guide shoe, insert float & 3 centrizers. Set @ 1450' KB. Cement w/500 sks lite w/2% CaCl + 1/4#/sks cello-flakes. Tail in w/200 sks Cl C + 2% CaCl. Plug down @ 4:47 p.m. 3/22/98. Circl 150 sks to pit.
3/26/98 TD 3864'.
3/27/98 Ran & cemented 4-1/2" csg. Set @ 3864'. Ran 6 centrizers. Cemented as follows: 600 sks 35/65 Poz-Lite w/8# salt & 1/4# cello-flake per sk. Tail in w/325 sks Cl C with 5/10% FL-52. Circl 50 sks to pit.

ACCEPTED FOR RECORD
(ORIG. SGD.) DAVID R. GLASS
JUL 27 1998
BLM

14. I hereby certify that the foregoing is true and correct

Signed Alexis Hernandez Title Engineering Technician

(This space for Federal or State office use)

Date 4/24/98

Approved by _____
Conditions of approval, if any: _____

Title _____ Date _____