

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) SAND OIL FRAC	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Monument, New Mexico  
(Place)

May 22, 1962  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Amerada Petroleum Corporation J. R. Phillips Well No. 8 in G  
(Company or Operator) (Unit)  
SW NE 1 20-S 36-E Monument Pool  
(40-acre Subdivision) T. R. NMPM, County.

### FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Plan to pull rods, pump and tubing. Set C. I. Cement retainer at approx. 3750' and squeeze the present perforations from 3762' to 3772' with 75 sacks reg. Incon cement. Perforate 7" casing by Lane Wells log from 3706' (-125') to 3726' (-139') with two bullet shots per foot and swab test. If necessary, sand oil frac the above perforations with 10,000 gals. crude oil and 5000# 20-40 sand and 5000# 10-20 sand using 1/20th lb. per gal of Mark II Adomite, swab test. In unsuccessful in closing water off, squeeze the above perforations with 50 sacks reg. Incon cement, perforate 7" casing from 3680' (-100') to 3695' (-115'), swab test. If necessary, sand oil frac these perforations with the same treatment as above and resume production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

AMERADA PETROLEUM CORPORATION

Company or Operator

By [Signature]  
Position Asst. District Superintendent

Send Communications regarding well to:

Name Amerada Petroleum Corporation

Address Drawer "D", Monument, New Mexico